

Q8 T 520 SAE 50

Mineral API CG-4 heavy-duty engine oil

Description

Q8 T 520 SAE 50 is an advanced heavy-duty engine oil. This product provides good lubrication after cold starting and thus limits engine wear, prohibits corrosion and protects against rust. It exceeds the normal standards of piston cleanliness for API CG-4.

Applications

Q8 T 520 SAE 50 can be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment. It can be used where API CG-4 is required. To be used where monograde engine oil is preferred

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.

Specifications & Approvals

API CG-4

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.895
Viscosity Grade	-	-	SAE 50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	197
Kinematic Viscosity, 100 °C	D 445	mm ² /s	18.5
Viscosity Index	D 2270	-	104
Total Base Number	D 2896	mg KOH/g	8.5
Pour Point	D 97	°C	-21
Flash Point, P-M	D 93	°C	214
Sulfated Ash	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.