

Q8 Formula Truck 8600 10W-40

Synthetic UHPD engine oil for ACEA E4/E6/E7/E9

Description

The Q8 Formula Truck 8600 10W-40 is a superior ultra high performance low SAPS heavy-duty engine oil. This product offers exceptional protection against engine wear, specifically against cam wear. It meets ACEA E6 specification along with specifications of various leading European OEM's such as Mercedes-Benz, MAN, Scania and Volvo.

Applications

Q8 Formula Truck 8600 10W-40 is developed for heavy-duty vehicles requiring the ACEA E4 / E6 / E7 / E9 and API CJ-4 specifications. It can be used in most Euro IV, Euro V and Euro VI diesel engines equipped with after treatment systems and operating on low sulphur diesel. It exceeds the requirements of more than 90% of the heavy-duty fleet such as IVECO, Scania, MAN, Mercedes-Benz, Cummins, Volvo, MTU or Caterpillar. Q8 Formula Truck 8600 10W-40 may be used where Volvo VDS-5 is prescribed though change interval must be adjusted accordingly and no VDS-5 fuel economy benefits are available. Please note Q8 Formula Truck 8600 10W-40 is not VDS-5 approved.

Benefits

- Outstanding combustion chamber cleanliness due to low sulphated ash level.
- Superior bio-fuel compatibility.
- Superior catalytic after treatment system (SCR) protection.
- Superior protection against engine wear.
- Extreme drain interval capability.

Specifications, recommendations and approvals

ACEA	E4	Liebherr	LH-00-ENG5C LA
ACEA	E6	MAN	M 3271-1
ACEA	E7	MAN	M 3477
ACEA	E9	MAN	M 3575
API	CJ-4	MB	226.9
Caterpillar	ECF-3	MB	228.51
Cummins	CES 20081	MTU	Type 3.1
Detroit Diesel	93K218	Mack	EO-O Premium Plus
Deutz	DQC IV-10 LA	Renault	RGD
Iveco	18-1804 TLS E6	Renault	RLD-3
Iveco	18-1809 NG2	Renault	RXD
JASO	DH-2	Scania	LA (Low Ash)
Liebherr	LH-00-ENG LA	Volvo	CNG
Liebherr	LH-00-ENG3A LA	Volvo	VDS-4

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,859
Viscosity Grade	-	-	SAE 10W-40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	89.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.6
Viscosity Index	D 2270	-	153
Total Base Number	D 2896	mg KOH/g	13.3
Pour Point	D 97	°C	-33
Flash Point, P-M	D 93	°C	226
Sulfated Ash	D 874	% mass	1.0
Borderline Pumping Temperature	D 3829	°C	-30

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.