

> Chain oil



Q8 Bizet AW 220

Chain and chainsaw oil with excellent performance

Description

Q8 Bizet AW 220 is a chain and chainsaw oil with an excellent performance and a low pour point. It contains well balanced extreme pressure additives that offer a low oil consumption. Q8 Bizet AW 220 has a strong adhesive oil film that leads to a longer lifetime of the chain slides. Its components are carefully selected with no harmful or unpleasant odours.

Applications

Q8 Bizet AW 220 is used in chains and slides of chainsaws. It is also perfect for chains, slides and guides in industrial applications.

Benefits

Improves the durability of the equipment thanks to its characteristics

Low oil consumption which leads to a lower maintenance cost

Features

Excellent adhesiveness Outstanding anti-wear characteristics Excellent thermal durability Outstanding friction diminution Neutral in odor

Specifications & Approvals

ISO

6743-1 L-AC

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	220
Density, 15 °C	D 4052	g/ml	0,891
Colour	D 1500	-	L 1.5
Kinematic Viscosity, 40 °C	D 445	mm²/s	220
Kinematic Viscosity, 100 °C	D 445	mm²/s	19.0
Viscosity Index	D 2270	-	97
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	270
Copper Strip, 3 h, 100 °C	D 130	-	1
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Bizet AW 220 should not be used for lubricating the engine of the chain saw.