

## Q8 Bizet AW 320

Chain and chainsaw oil with excellent performance

### Description

Q8 Bizet AW 320 is a chain and chainsaw oil with an excellent performance and a low pour point. It contains well balanced extreme pressure additives that offer a low oil consumption. Q8 Bizet AW 320 has a strong adhesive oil film that leads to a longer lifetime of the chain slides. Its components are carefully selected with no harmful or unpleasant odours.

### Applications

Q8 Bizet AW 320 is used in chains and slides of chainsaws. It is also perfect for chains, slides and guides in industrial applications.

### Benefits

Improves the durability of the equipment thanks to its characteristics

Low oil consumption which leads to a lower maintenance cost

### Features

Excellent adhesiveness

Outstanding anti-wear characteristics

Excellent thermal durability

Outstanding friction diminution

Neutral in odor

### Specifications & Approvals

ISO 6743-1 L-AC

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	320
Density, 15 °C	D 4052	g/ml	0,896
Colour	D 1500	-	L 2.0
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	320
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	24.3
Viscosity Index	D 2270	-	97
Total Acid Number	D 974	mg KOH/g	0.37
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	280
Copper Strip, 3 h, 100 °C	D 130	-	1
Texture	Visual	-	Stringy
Four Ball Wear, 392 N, 75 °C, 1200 rpm	D 4172	mm	0.4

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Q8 Bizet AW 320 should not be used for lubricating the engine of the chain saw.