

Q8 Gear Oil V 75W-80

Synthetic Volvo transmission fluid

Description

Q8 Gear Oil V 75W-80 is a superior synthetic transmission fluid, offering extended drain intervals and best-in-class performance in demanding conditions. This product provides easy gear shifting and exceptional protection in high temperature conditions due to constant film strength. Low viscosity characteristics optimize transmission efficiency and fuel economy.

Applications

Q8 Gear Oil V 75W-80 is especially designed for Volvo 97307 long drain intervals. This product meets the requirements of many commercial vehicle OEMs and/or gearbox manufacturers including MAN, ZF, DAF, IVECO, Eaton, Renault and Volvo.

Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.

Specifications, recommendations and approvals

API	GL-4	MB	235.4
DAF		Renault	
Eaton/Fuller	Europe Extended drain (300.000 km)	Volvo	97305
Iveco		Volvo	97307 *
MAN	341 Type E3	ZF	TE-ML 01L
MAN	341 Type E4	ZF	TE-ML 02L
MAN	341 Type Z3	ZF	TE-ML 08
MAN	341 Type Z4	ZF	TE-ML 16K

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,862
Viscosity Grade	-	-	SAE 75W-80
Kinematic Viscosity, 40 °C	D 445	mm ² /s	58.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.8
Viscosity Index	D 2270	-	154
Brookfield Viscosity, -40 °C	D 2983	Pa.s	47.0
Pour Point	D 97	°C	-33
Flash Point, P-M	D 93	°C	221

The figures above are not a specification. They are typical figures obtained within production tolerances.