

Q8 Hunt 46

Sustainable hydraulic fluid

Description

Q8 Hunt 46 is a sustainable hydraulic fluid for a wide range of hydraulic applications. By using this fluid, natural resources will be saved and the carbon footprint will significantly drop compared to common hydraulic oils. Q8 Hunt 46 meets the industrial hydraulic standard DIN 51524-2 HLP thanks to its combination of purified base oils and carefully selected additives.

Applications

Q8 Hunt 46 is used in a wide range of industrial hydraulic applications. The renewable lubricant is also applied in hydraulic systems operating in winter conditions (up to -30°C) and in mobile hydraulic systems such as cranes, excavators and other off-road equipment.

Benefits

Lower downtime and an improved maintenance efficiency

Limited impact on the environment

Features

Includes zinc-based additives

Optimum wear protection

High filtration properties

Highly environmental sustainable

Specifications & Approvals

DIN 51524-2 HLP **ISO** 11158 HM

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	864
Kinematic Viscosity, 40 °C	D 445	mm ² /s	45.0
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	7.0
Viscosity Index	D 2270	-	>116
Flash Point, COC	D 92	°C	240
Pour Point	D 97	°C	-30
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40/40/0 (10min)
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.