

Q8 Hunt HV 32

Sustainable hydraulic fluid

Description

Q8 Hunt HV 32 is an sustainable hydraulic fluid for a wide range of hydraulic applications. By using this fluid, natural resources will be saved and the carbon footprint will significantly drop compared to common hydraulic oils. Q8 Hunt HV 32 meets the industrial hydraulic standard DIN 51524-3 HVLP thanks to its combination of purified base oils and carefully selected additives.

Applications

Q8 Hunt HV 32 is used in a wide range of industrial hydraulic applications operating in a broad temperature range. The renewable lubricant is also applied in hydraulic systems operating in winter conditions (up to -42°C) and in mobile hydraulic systems such as cranes, excavators and other off-road equipment.

Benefits

Lower downtime and an improved maintenance efficiency

Limited impact on the environment

Features

Zinc included technology

High viscosity index

Advanced anti-wear characteristics

Highly environmental sustainable

Specifications & Approvals

DIN 51524-3 HVLP ISO 11158 HV

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0.857
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	31.5
Kin. Viscosity Base Oil at 100 °C	D 445	mm ² /s	6.3
Viscosity Index	D 2270	-	152
Flash Point, COC	D 92	°C	210
Pour Point	D 97	°C	-42
FZG Test, A/8.3/90	DIN 51354	load stage	12

The figures above are not a specification. They are typical figures obtained within production tolerances.