

Q8 Rossini HMG 32

Superior food grade synthetic hydraulic fluid

Description

The superior Q8 Rossini HMG 32 is perfect for usage in the food industry where fluids may come in contact with food. Its advanced filterability and demulsibility makes this lubricant reliable for sensitive hydraulic servo systems that demand a clean working environment. The Q8 Rossini HMG 32 has an exceptional thermal and oxidation stability, which leads to an extended lubricant life time.

Applications

It is used in applications where NSF-H1 lubricants are required. The Q8 Rossini HMG 32 is perfect hydraulic systems used in the pharmaceutical and food industry like beverage production and packaging.

Benefits

Limited impact on the environment

Lower downtime and an improved maintenance efficiency

Features

Safe to use in food industry

Doesn't contain hazardous components

Superior synthetic oil

Extremely appropriate for use in a wide range of temperatures

Outstanding flow characteristics

Specifications & Approvals

DIN 51524-3 HVLP ISO 11158 HV

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	32
Density, 15 °C	D 4052	g/ml	0,829
Colour	D 1500	-	L 0.5
Kinematic Viscosity, 40 °C	D 445	mm ² /s	31.4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.0
Viscosity Index	D 2270	-	140
Pour Point	D 97	°C	<-60
Flash Point, COC	D 92	°C	240

The figures above are not a specification. They are typical figures obtained within production tolerances.