

## Q8 SuperGear V Plus 75W-90

Synthetic high performance transmission fluid

### Description

Q8 SuperGear V Plus 75W-90 is a synthetic high performance transmission fluid specially developed to meet the Volvo 97315 specification. This product offers fuel savings, limits synchromesh wear, provides smooth gear shifting and facilitates cold starting. It keeps the transmission clean, protects against rust, corrosion and wear which results in extended equipment life.

### Applications

Q8 SuperGear V Plus 75W-90 can be used in manual transmissions of heavy duty vehicles that require the Volvo 97315 specification.

### Benefits

- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.

### Specifications, recommendations and approvals

**Volvo** **97315**

Color code blue = officially approved

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,871
Viscosity Grade	-	-	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	133.3
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	17.6
Viscosity Index	D 2270	-	146
Brookfield Viscosity, -40 °C	D 2983	Pa.s	14.8
Pour Point	D 97	°C	-38
Flash Point, P-M	D 93	°C	192

The figures above are not a specification. They are typical figures obtained within production tolerances.