

Q8 da Vinci 6

Light demoulding oil with exceptional surface finishing

Description

Q8 da Vinci 6 is a superior demoulding oil with anti-rust inhibitors for steel moulds. It's solvent free and easily applicable. The reactive layer in the oil creates a layer between the concrete and the mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci provides an exceptional smooth surface finish of the concrete and a clean mould without staining or dust.

Applications

Q8 da Vinci 6 is used for demoulding concrete foundation piles, tiles and on-site elements such as floors, stairs, balconies and prefab sewage pipes. It is applied in steel and plywood moulds. Q8 da Vinci 6 is highly recommended on site building constructions for direct release demoulding.

Benefits

Leads to an improved durability of the finished product quality

Extremely effective demoulding operation

Features

Outstanding quality of the surface

Light colour

Exceptional anti-rust properties

Enhanced with special additives

Prevents sticking

Extremely handy to apply

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0,836
Kinematic Viscosity, 40 °C	D 445	mm ² /s	6.0
Pour Point	D 97	°C	-21
Flash Point, COC	D 92	°C	130
Rust Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

For use in cold temperatures, we recommend Q8 da Vinci P series. Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.