

Q8 Chain Oil 150

Advanced chain and chainsaw oil

Description

Q8 Chain oil 150 is an advanced chain and chainsaw oil with low oil consumption and high wear protection through the adhesive oil film. Its excellent components are carefully selected to prevent harmful or unpleasant odours. Q8 Chain oil 150 has optimum wear-, corrosion- and rust protection.

Applications

Q8 Chain Oil 150 is used in chains and slides of chainsaws. It is perfect for chains, slideways and guides in industrial applications.

Benefits

- Improves the durability of the equipment thanks to its characteristics
- Advanced adhesive characteristics
- Excellent spreadability
- Advanced performance against wear

Specifications & Approvals

ISO 6743-1 L-AC

Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	150
Density, 15 °C	D 4052	g/ml	0,887
Colour	D 1500	-	L 2.0
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14.60
Kinematic Viscosity, 40 °C	D 445	mm ² /s	150.0
Viscosity Index	D 2270	-	96
Pour Point	D 97	°C	-12
Flash Point, COC	D 92	°C	262
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Chain Oil 150 should not be used for lubricating the engine of the chain saw.