

Q8 Gear Oil V LD 75W-90

Full synthetic API GL-4, manual transmission fluid for Volvo, Mercedes and MAN

Description

Q8 Gear Oil V LD 75W-90 is a superior full synthetic transmission fluid providing excellent lubrication in high load transmissions. This product offers class-leading thermal stability and fuel saving properties. Meets the API GL-4 specification and developed to meet Volvo 97315, Volvo 97319 and MB 235.11

Applications

Q8 Gear Oil V LD 75W-90 is especially designed for heavy duty transmissions requiring MB 235.11. The lubricant can also be recommended for all vehicles that require a 75W-90 viscosity oil and when the API GL-4 or MAN 341 Z4/E3, ZF 02L and Volvo 97315/97319 specifications are prescribed by the manufacturer

Benefits

- Full synthetic formulation to provide an extreme thermal stability.
- Outstanding protection against wear and extends component life.
- Outstanding protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.
- Superior gear protection under heavy duty conditions.

Specifications, recommendations and approvals

API	GL-4	Renault	
DAF		Volvo	97315
Eaton/Fuller	Europe Extended drain (300.000 km)	Volvo	97319
Iveco		ZF	TE-ML 01L
MAN	341 Type E3	ZF	TE-ML 02L
MAN	341 Type Z4	ZF	TE-ML 08
MB	235.11	ZF	TE-ML 16K
MB	235.4		

Properties

	Method	Unit	Typical
Density, 15° C (60° F)	D 4052	g/ml	0,868
Viscosity Grade	-	-	75W-90
Kinematic Viscosity, 40 °C	D 445	mm²/s	119
Kinematic Viscosity, 100 °C	D 445	mm²/s	17.8
Viscosity Index	D 2270	-	165
Brookfield Viscosity, -40 °C	D 2983	Pa.s	55
Flash Point, P-M	D 93	°C	221
Pour Point	D 97	°C	-42

The figures above are not a specification. They are typical figures obtained within production tolerances.