

Q8 Gear Oil V LD 75W-80

Synthetic Volvo long drain transmission fluid

Description

Q8 Gear Oil V LD 75W-80 is a superior fully synthetic transmission fluid, offering extended drain intervals and best-in-class performance in demanding conditions. This product provides easy gear shifting and exceptional protection in high temperature conditions due to constant film strength. Low viscosity characteristics optimize transmission efficiency and fuel economy.

Applications

Q8 Gear Oil V LD 75W-80 is especially designed for Volvo 97318 long drain intervals. This product meets the requirements of many commercial vehicle OEMs and/or gearbox manufacturers including MAN, ZF, DAF, IVECO, Eaton, Renault and Volvo long drain.

Benefits

- Superior protection against corrosion under all weather conditions.
- Superior protection against rust and corrosion.
- Excellent easy gear shifting at low temperatures and extended equipment life.

Specifications, recommendations and approvals

API	GL-4	Renault	
DAF		Volvo	97305
Eaton/Fuller	Europe Extended drain (300.000 km)	Volvo	97307
Iveco	18-1807 MGS1	Volvo	97318
MAN	341 Type E3	ZF	TE-ML 01L
MAN	341 Type Z4	ZF	TE-ML 02L
MB	235.11	ZF	TE-ML 08
MB	235.4	ZF	TE-ML 16K

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,864
Viscosity Grade	-	-	75W-80
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	10.1
Brookfield Viscosity, -40 °C	D 2983	Pa.s	20.0
Flash Point, P-M	D 93	°C	221
Pour Point	D 97	°C	-57

The figures above are not a specification. They are typical figures obtained within production tolerances.