

## Q8 Stravinsky N 46

High performance refrigeration compressor oil

### Description

Q8 Stravinsky N 46 is a high performance refrigeration compressor oil. It is developed with premium selected naphtenic base fluid. The product is recommended for use with CFC-, HCFC- or traditional type refrigerant (such as ammonia). The low pour point and outstanding fluidity at low temperature ensure problem-free operations.

### Applications

Reciprocating- and rotary refrigerator compressors Industrial applications such as refrigerators and freezers Refrigerating systems handling CFC-, HCFC- or traditional type refrigerant (such as ammonia)

#### Features

#### Benefits

##### Enhanced technology

Fully compatible with mineral oils and normally used elastomer/plastic materials in compressor equipment

##### Extended drain

Advanced oxidative stability, guaranteeing long oil life under continuous and severe operating conditions

##### Safety

Tailored to the specific needs of your equipment to ensure safe and reliable operations

### Properties

|                             | Method | Unit               | Typical |
|-----------------------------|--------|--------------------|---------|
| ISO Viscosity Grade         | -      | -                  | 46      |
| Density, 15 °C              | D 4052 | g/ml               | 909     |
| Kinematic Viscosity, 40 °C  | D 445  | mm <sup>2</sup> /s | 46.0    |
| Kinematic Viscosity, 100 °C | D 445  | mm <sup>2</sup> /s | 5.6     |
| Flash Point, COC            | D 92   | °C                 | 190     |

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky N, it is recommended to flush the compressor lubricant system.