

Q8 T 520 SAE 20

Mineral API CG-4 heavy-duty engine oil

Description

Q8 T 520 SAE 20 is a heavy-duty engine oil formulated to suit the needs of old generation vehicles with turbocharged engines. The oil has been formulated with a special package of additives and detergents/dispersants. It provides advanced anti-wear capacity, optimum lubrication and keeps the engine clean.

Applications

Q8 T 520 SAE 20 can be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment. It's developed for old generation vehicles having turbocharged engines. To be used where monograde engine oil is preferred

Benefits

- High protection against rust and corrosion.
- Premium protection against engine wear.

Specifications, recommendations and approvals

Allison
Caterpillar

C-3
TO-2

Voith

Retarder

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.883
Viscosity Grade	-	-	SAE 20W-20
Kinematic Viscosity, 40 °C	D 445	mm ² /s	61.3
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.6
Viscosity Index	D 2270	-	114
Total Base Number	D 2896	mg KOH/g	8.5
Pour Point	D 97	°C	-30
Flash Point, P-M	D 93	°C	210
Sulfated Ash	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.