

Q8 Antifreeze Long Life

Superior long life antifreeze

Description

Q8 Antifreeze Long Life is a superior fluid that protects against freezing, boiling and corrosion of the cooling system. When mixed with water, the antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Antifreeze Long Life is obtained by non-depleting corrosion inhibitors.

Applications

Q8 Antifreeze Long Life is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Benefits

- Exceptional long life protection against all forms of corrosion.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime
- Superior and extended corrosion protection due to synergistic effects.
- Best-in-class cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.

Specifications, recommendations and approvals

ASTM	D 3306	Komatsu	KES 07.892
ASTM	D 4656	Liebherr	MD1-36-130
ASTM	D 4985	MAN	324 Type SNF
ASTM	D 6210	MB	325.3
Case New Holland	MAT 3624	MTU	MTL 5048
Cummins	CES 14439	Mitsubishi	MHI
Cummins	CES 14603	Opel/Vauxhall	GMW 3420
DAF	74002	Renault	41-01-001/S Type D
Deutz	DQC CB-14	SAE	J 1034
Ford	M97B44-D	VAG	VW TL 774 D (G12)
INNIO Jenbacher	TA 1000-0201	VAG	VW TL 774 F (G12+)
JIS	K 2234		

Color code blue = officially approved

* Pending approval

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	1.116
Colour	Visual	-	Orange-red
Freezing Protection 33-67%	D 1177	°C	-18
Freezing Protection 50-50%	D 1177	°C	-38
Equilibrium boiling point	D 1120	°C	180

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Minimum 33% Q8 Antifreeze Long Life should be in the coolant solution to ensure proper corrosion protection. Normally 50% solutions are recommended. Dilution with deionized water is preferred. Replacement of the antifreeze is recommended after 4 years. Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.