

## Q8 Auto CVT EVO

Synthetic CVT fluid

### Description

Q8 Auto CVT EVO is an outstanding multi-vehicle Continuous Variable Transmission fluid for modern transmissions. This product is shear stable, offers extended drain intervals, excellent performance reserve and prevents slipping belts/clutches and breakdowns. It maintains high steel-steel friction and oil pressure, and provides a strong oil film.

### Applications

Q8 Auto CVT EVO is applicable for CVT transmissions in passenger cars. It meets the JASO LVFA specification. The product is based on new technology and exceeds the requirements of all major OEMs such as Toyota, Nissan, Mitsubishi, Subaru, Suzuki, Hyundai, Honda, Daihatsu, Mini, BMW, Chrysler and GM.

### Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.
- Excellent metal-metal friction and torque transfer
- Excellent oxidation and thermal stability
- Incorporates well balanced friction modifier system

### Specifications, recommendations and approvals

BAIC	CVTF-EX1	Mitsubishi	Diaqueen CVT Fluid J4
BMW/MINI	83 22 0 136 376	Mitsubishi	Diaqueen CVT Fluid J4+
BMW/MINI	83 22 0 429 154	Mitsubishi	Diaqueen SP-III
BMW/MINI	CVT V1	Nissan	KTF-1
BMW/MINI	EZL 799	Nissan	NS-1
BMW/MINI	EZL 799A	Nissan	NS-2
Chery	CVT	Nissan	NS-3
Chrysler	CVT+4	Punch	CVTF-EX1
Chrysler	NS-2	Renault	Matic CVT
DFSK	CVTF-EX1	Renault	Matic CVT CK
Daihatsu	Ammix CVTF DFE	Renault	Matic CVT FK
Daihatsu	Ammix CVTF DC	Renault	Matic CVT SK
Daihatsu	Ammix CVTF DFC	Shell	Green 1V
Daihatsu	Fluid TC	Subaru	CV-30
Dodge	CVTF+4	Subaru	K0421Y0700
Dodge	NS-2	Subaru	K0425Y0710
Fiat	Tutela Car CVT NG	Subaru	K0425Y0711
Fujjyuuko	i-CVTF FG	Subaru	Lineartronic High Torque (HT) CVT Fluid
GM	DEX-CVT	Subaru	Lineartronic chain CVT
Honda	CVT	Subaru	Lineartronic chain CVT II Fluid
Honda	Fit	Subaru	NS-2
Honda	HCF2	Suzuki	CVT Green 1
Honda	HMMF	Suzuki	CVT Green 1V
Honda	Jazz	Suzuki	CVT Green 2
Honda	Z-1 (CVT model)	Suzuki	CVTF 3320
Hyundai/Kia	CVT-1	Suzuki	CVTF 4401
Hyundai/Kia	SP-III (CVT model)	Suzuki	CVTF TC
Idemitsu	CVTF-EX1	Suzuki	NS-2
Lexus	Fluid FE	Toyota	CVTF FE
Lexus	Fluid TC	Toyota	CVTF TC
MB	236.20	VAG	Audi Multitronic
MG/Rover	EM-CVT	VAG	VW G 052 180
Mazda	JWS 3320	VAG	VW G 052 516
Mitsubishi	CVTF ECO J4	VAG	VW TL 521 16

Mitsubishi  
Mitsubishi

CVTF-J4+  
Diaqueen CVT Fluid J1

VAG  
Volvo

VW TL 521 80  
CVT 4959

## Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,849
Kin. Viscosity Base Oil at 100 °C	D 445	mm <sup>2</sup> /s	7.0
Kin. Viscosity Base Oil at 40 °C	D 445	mm <sup>2</sup> /s	32.3
Viscosity Index	D 2270	-	185
Brookfield Viscosity, -40 °C	D 2983	Pa.s	10
Flash Point, COC	D 92	°C	190
Pour Point	D 97	°C	-45

The figures above are not a specification. They are typical figures obtained within production tolerances.

## Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.