

Q8 Auto JK

Synthetic automatic transmission fluid designed for Aisin Warner

Description

Q8 Auto JK is an outstanding multifunctional automatic transmission fluid. The product offers excellent thermal stability and improves overall transmission durability and cleanliness. It is specifically designed for Aisin Warner automatic transmissions.

Applications

Q8 Auto JK is an automatic transmission oil for passenger cars, specifically designed for Aisin Warner transmissions. It meets the requirements of Japanese and Korean manufacturers and is recommended for SUV's and light commercial vehicles.

Benefits

- Outstanding protection against wear and extends component life.
- Optimal friction characteristics even at low temperatures
- Excellent oxidation and thermal stability
- Outstanding internal friction reduction.

Specifications, recommendations and approvals

Aisin Warner	JWS 3309 (T-IV)	Mitsubishi	Diaqueen SP-III (except in CVT's)
Aisin Warner	JWS 3324 (WS)	Nissan	Matic C
Aisin Warner	JWS AW-1	Nissan	Matic D
Allison	C-4	Nissan	Matic J
Allison	TES-228	PSA	JWS 3309
Chrysler	ATF+3	Porsche	P/N 000 043 205 28
Chrysler	ATF+4	Saab	3309
Chrysler	MS-9602	Subaru	ATF-HP
Daihatsu	Alumix ATF Multi	Subaru	K0710Y0700
Ford	M2C166-H	Suzuki	ATF 3314
Ford	M2C202-B	Suzuki	ATF 3317
Ford	M2C919-E	Toyota	D-II
Ford	M2C924-A	Toyota	T-I
Ford	Mercon	Toyota	T-II
Ford	Mercon V	Toyota	T-III
GM	9986195 (Aisin AW, JWS 3309)	Toyota	T-IV
GM	Dexron III G	Toyota	WS
GM	Dexron III H	VAG	VW G 052 025
Honda	Z-1 (except in CVT)	VAG	VW G 052 162
Hyundai/Kia	SP-III (except in CVT's)	VAG	VW G 055 025
Hyundai/Kia	SP-IV	Volvo	P/N 1161540
Isuzu	Besco ATF-III	ZF	8HP
JASO	M315 Type 1A	ZF	TE-ML 03D
MAN	339 Type V2	ZF	TE-ML 04D
MAN	339 Type Z2	ZF	TE-ML 09
MAN	339 Type Z3	ZF	TE-ML 14A
MB	236.10	ZF	TE-ML 14B
MB	236.9	ZF	TE-ML 16L
MB	236.91	ZF	TE-ML 17C
Mazda	ATF M-V		

* Pending approval

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,851
Kinematic Viscosity, 40 °C	D 445	mm ² /s	35.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.2
Viscosity Index	D 2270	-	174
Brookfield Viscosity, -40 °C	D 2983	Pa.s	18.4
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	212

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.