Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

SAFETY DATA SHEET

Q8 CHF 22S



SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1 Product identifier : Q8 CHF 22S **Product name** 1.2 Relevant identified uses of the substance or mixture and uses advised against Material uses : Lubricating oil for hydraulic equipment 1.3 Details of the supplier of the safety data sheet Supplier : Kuwait Petroleum Companies in the Benelux Company Office: Brusselstraat 59, 2018 Antwerp, Belgium Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium Tel. +32 3 247 38 11, Fax +32 3 216 03 42 Manufacturer / Distributor : Kuwait Petroleum Belgium N.V./S.A. Q8Oils Italia S.r.l. 1 Petroleumkaai 7 Via Volpedo 2 B-2020 Antwerp 15050 Castellar Guidobono (AL) Belgium Italy e-mail address of person responsible for this SDS : SDSinfo@Q8.com, communication preferably in English only. **PCN Information contact** : PCNinfo@Q8.com, communication preferably in English only. 1.4 Emergency telephone number Europe : +44 (0) 1235 239 670 CARECHEM24 **Global (English only)** : +44 (0) 1865 407 333 National advisory body/Poison Center **Belgium** : Poison Centre : +32 (0)70 245 245

SECTION 2: Hazards identification

2.1 Classification of the sub	stance or mixture		
Product definition	: Mixture		
Classification according to	Regulation (EC)	No. 1272/2008 [CLP/GHS]	
CUTE TOXICITY (inhalatic	on)	Category 4	H332
ASPIRATION HAZARD		Category 1	H304
The product is classified as l	hazardous accordin	g to Regulation (EC) 1272/2008 as amended	
Ingredients of unknown toxicity	: None.		
Ingredients of unknown ecotoxicity	: None.		
See Section 16 for the full te	xt of the H stateme	nts declared above.	

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



SECTION 2: Hazards identification

Signal word	:	Danger
Hazard statements	1	H304 - May be fatal if swallowed and enters airways. H332 - Harmful if inhaled.
Precautionary statements		
General	:	 P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	1	P271 - Use only outdoors or in a well-ventilated area. P261 - Avoid breathing vapor.
Response	:	₱304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
Storage	:	P405 - Store locked up.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Dec-1-ene, dimers, hydrogenated Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based
Supplemental label elements	1	Contains Ethanol, 2,2'-iminobis-, N-tallow alkyl derivs. and methyl methacrylate. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Detergents - Regulation (EC) No 648/2004	:	Not applicable.
Special packaging requirem	ien	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Yes, applicable.
Tactile warning of danger	;	Yes, applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Øec-1-ene, dimers, hydrogenated	REACH #: 01-2119493069-28 EC: 500-228-5 CAS: 68649-11-6	≥75 - ≤90 }	Acute Tox. 4, H332 Asp. Tox. 1, H304	ATE [Inhalation (gases)] = 4500 ppm	[1]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0	≥25 - ≤50 S	Asp. Tox. 1, H304	-	[1] [2]
Date of issue/Date of revision	: 21-06-2023	Date of previous is	ssue : 17-10-2020	Version : 1.	01 2/1

SECTION 3: Composition/information on ingredients

	Index: 649-482-00-X				
Ethanol, 2,2'-iminobis-, N- tallow alkyl derivs.	EC: 263-177-5 CAS: 61791-44-4	<1	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	ATE [Oral] = 500 mg/kg	[1]
methyl methacrylate	REACH #: 01-2119452498-28 EC: 201-297-1 CAS: 80-62-6 Index: 607-035-00-6	<1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures	4.1	Description	of first aid	measures
---------------------------------------	-----	-------------	--------------	----------

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse. High pressure skin injections are serious medical emergencies. Injury will not appear serious at first. Within a few hours, tissue will become swollen, discolored and extremely painful.
Ingestion	: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

Q8 CHF 22S			
SECTION 4: First aid	SECTION 4: First aid measures		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.		
4.2 Most important sympton	ns and effects, both acute and delayed		
Over-exposure signs/symp	itoms		
Eye contact	: No specific data.		
Inhalation	: No specific data.		
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking		
Ingestion	: Adverse symptoms may include the following: nausea or vomiting		

4.3 Indication of any immediate medical attention and special treatment needed	
--	--

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large
	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media		
Suitable extinguishing media	:	Use dry chemical, CO ₂ , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	:	Do not use water jet.
5.2 Special hazards arising f	from	the substance or mixture
Hazards from the substance or mixture	:	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters		Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

SECTION 6: Accidental release measures

For emergency responde	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials	o for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
└ubricating oils (petroleum), C15-30,	Limit values (Belgium, 5/2021). []
hydrotreated neutral oil-based	TWA: 5 mg/m ³ 8 hours. Form: mist
	STEL: 10 mg/m ³ 15 minutes. Form: mist
methyl methacrylate	Limit values (Belgium, 5/2021).
	TWA: 50 ppm 8 hours.
	TWA: 208 mg/m ³ 8 hours.
	STEL: 416 mg/m ³ 15 minutes.
	STEL: 100 ppm 15 minutes.
	EU OEL (Europe, 10/2019). Notes: list of indicative
	occupational exposure limit values
	TWA: 50 ppm 8 hours.
	STEL: 100 ppm 15 minutes.
Recommended monitoring : If this proc	luct contains ingredients with exposure limits, personal, workplace

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
₽ec-1-ene, dimers, hydrogenated	DNEL	Short term	50 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Short term	60 mg/m³	Workers	Systemic
		Inhalation			
Lubricating oils (petroleum), C15-30,	DNEL	Long term Oral	0.74 mg/	General	Systemic
hydrotreated neutral oil-based			kg bw/day	population	
	DNEL	Long term Dermal	0.97 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.19 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	2.73 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
methyl methacrylate	DNEL	Long term Dermal	8.2 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	13.67 mg/	Workers	Systemic
			kg bw/day	_	
	DNEL	Long term	74.3 mg/m ³		Systemic
		Inhalation		population	
	DNEL	Long term	104 mg/m³	General	Local
		Inhalation		population	
	DNEL	Long term	208 mg/m ³	Workers	Local
		Inhalation			
	DNEL	Long term	208 mg/m³	Workers	Systemic
	<u> </u>	Inhalation			
e of issue/Date of revision : 21-0	6-2023	Date of previous issue	: 17-10-2	020 Ve	rsion : 1.01

SECTION 8: Exposure controls/personal protection

DNEL	Short term Dermal	1.5 mg/cm ²	General	Local
			population	
DNEL	Long term Dermal	1.5 mg/cm ²	General	Local
			population	
DNEL	Short term Dermal	1.5 mg/cm ²	Workers	Local
DNEL	Long term Dermal	1.5 mg/cm ²	Workers	Local
DNEL	Long term Oral	8.2 mg/kg	General	Systemic
		bw/day	population	
DNEL	Short term	208 mg/m ³	General	Local
	Inhalation		population	
DNEL	Short term	416 mg/m ³	Workers	Local
	Inhalation			

PNECs

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Individual protection meas	<u>ures</u>
Hygiene measures	: Do not ingest. If swallowed then seek immediate medical assistance. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

<u>Appearance</u>					
Physical state	1	Liquid. [[Oily liquid.]		
Appearance	: Clear.				
Color	: Green. [Dark]				
Odor	: Characteristic.				
Odor threshold	: Not available.				
Melting point/freezing point	1	Not app	licable.		
Pour point	1	- 55°C (-	-67°F) [ASTM D 59	950]	
Initial boiling point and boiling range	1	>300°C	(>572°F)		
Flammability	1	Not app	licable.		
Lower and upper explosion limit	1	Lower: (Upper: (
Flash point	1	Closed	cup: 156°C (312.8	°F) [ASTM D 93]	
Auto-ignition temperature	:				
Ingredient name			°C	°F	Method
Dec-1-ene, dimers, hydrogenated					4.0TM D 0450
Dec-1-ene, uniters, hydrogenated			324	615.2	ASTM D 2158
		>300°C		615.2	ASTM D 2158
Decomposition temperature	:	>300°C		615.2	ASTM D 2158
Decomposition temperature pH	: : :	<mark>M</mark> ot app	licable.		
Decomposition temperature		<mark>M</mark> ot app	licable.	^{615.2} 19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity	: : :	<mark>M</mark> ot app	licable. tic (40°C (104°F)):		
Decomposition temperature pH Viscosity Solubility(ies)	: : :	Not app Kinema	licable. tic (40°C (104°F)): t		
Decomposition temperature pH Viscosity Solubility(ies) Media	::	Not app Kinema	licable. tic (40°C (104°F)): t bluble		
Decomposition temperature pH Viscosity Solubility(ies) Media	: :	Mot app Kinema Resul Not sc	licable. tic (40°C (104°F)): t bluble bluble		
Decomposition temperature pH Viscosity Solubility(ies) Media fold water hot water Partition coefficient: n-octanol/	::	Not app Resul Not so Not so Not app	licable. tic (40°C (104°F)): t bluble bluble	19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity Solubility(ies) Media Cold water hot water Partition coefficient: n-octanol/ water	::	Not app Kinema Result Not so Not app Kot app K	licable. tic (40°C (104°F)): t bluble bluble licable.	19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity Solubility(ies) Media Øold water hot water Partition coefficient: n-octanol/ water Vapor pressure	::	Not app Kinema Result Not so Not app Kot app K	licable. tic (40°C (104°F)): t bluble bluble licable. 001 kPa (<0.00000 cm³ [20°C (68°F)] [<i>i</i>	19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity Solubility(ies) Media Cold water hot water Partition coefficient: n-octanol/ water Vapor pressure Density	::	Not app Kinema Result Not so Not app Kot app Ko	licable. tic (40°C (104°F)): t bluble bluble licable. 001 kPa (<0.00000 cm³ [20°C (68°F)] [<i>i</i> ilable.	19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity Solubility(ies) Media Øold water hot water Partition coefficient: n-octanol/ water Vapor pressure Density Vapor density	::	Not app Kinema Not sc Not sc Not app 0.0000 82 g/c Not ava	licable. tic (40°C (104°F)): t bluble bluble blicable. 001 kPa (<0.00000 cm³ [20°C (68°F)] [<i>i</i> ilable.	19 mm²/s (19 cSt)	
Decomposition temperature pH Viscosity Solubility(ies) Media Fold water hot water Partition coefficient: n-octanol/ water Vapor pressure Density Vapor density Explosive properties	::	Not app Kinema Result Not so Not app Kot app Kot app Kot app Kot app Kot app Not so Not app	licable. tic (40°C (104°F)): t bluble bluble blicable. 001 kPa (<0.00000 cm³ [20°C (68°F)] [<i>i</i> ilable.	19 mm²/s (19 cSt)	

9.2 Other information

Not available.

SECTION 10: Stability and reactivity

10.1 Reactivity	÷	No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	:	The product is stable.
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.

SECTION 10: Stabili	ty and reactivity	
10.4 Conditions to avoid	: No specific data.	

10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials
	Strong oxidizing materials

10.6 Hazardous: Under normal conditions of storage and use, hazardous decomposition productsdecomposition productsshould not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
methyl methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m³	4 hours
	LD50 Dermal	Rabbit	>5 g/kg	-
	LD50 Oral	Rat	7872 mg/kg	-

Conclusion/Summary : Not available.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
🛛 8 CHF 22S	N/A	N/A	7411.8	18.1	2.5
Dec-1-ene, dimers, hydrogenated	N/A	N/A	4500	11	1.5
Ethanol, 2,2'-iminobis-, N-tallow alkyl derivs.	500	N/A	N/A	N/A	N/A
methyl methacrylate	7872	N/A	N/A	78	N/A

Irritation/Corrosion	
Conclusion/Summary	: Not available.
Sensitization	
Conclusion/Summary	: Not available.
<u>Mutagenicity</u>	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.
Specific target organ toxic	ity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methyl methacrylate	Category 3	-	Respiratory tract irritation

<u>Specific target organ toxicity (repeated exposure)</u> Not available.

Aspiration hazard

Product/ingredient name	Result
✓ec-1-ene, dimers, hydrogenated Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Date of issue/Date of revision

SECTION 11: Toxicological information

Information on the likely routes of exposure	: Not available.
Potential acute health effects	<u>1</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: Harmful if inhaled.
Skin contact	: Defatting to the skin. May cause skin dryness and irritation.
Ingestion	: May be fatal if swallowed and enters airways.
Symptoms related to the phy	sical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
Delayed and immediate effect	ts and also chronic effects from short and long term exposure
<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health eff	ects
Not available.	
Conclusion/Summary	: Not available.
General	: Prolonged or repeated contact can defat the skin and lead to irritation, cracking

General	 Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/ or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.

Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

- **11.2.1 Endocrine disrupting properties**
- Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
methyl methacrylate	Acute LC50 130000 µg/l Fresh water	Fish - Pimephales promelas - Adult	96 hours
Conclusion/Summary	: Not available.		

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Dec-1-ene, dimers, hydrogenated	>6.5	-	high
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	>6	-	high
methyl methacrylate	1.38	-	low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European w	aste cata	loque	(FWC)
		logue	

Waste code	Waste designation		
13 01 11*	synthetic hydraulic oils		
Packaging			
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. bulk according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Other EU regulations		
Industrial emissions (integrated pollution prevention and control) - Air	:	Not listed
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed
Ozone depleting substand	ces	<u>(1005/2009/EU)</u>
Not listed.		
Prior Informed Consent (F Not listed.	<u>PIC)</u>	<u>(649/2012/EU)</u>

SECTION 15: Regulat	to	ry information
Persistent Organic Pollutar Not listed.	nts	<u>i</u>
Seveso Directive		
This product is not controlled	l ui	nder the Seveso Directive.
National regulations		
<u>Germany</u>		
Hazard class for water (WGK)	:	2
Switzerland		
VOC content	:	Exempt.
International regulations		
Chemical Weapon Convention Not listed.	<u>on</u>	List Schedules I, II & III Chemicals
Montreal Protocol Not listed.		
Stockholm Convention on P Not listed.	<u>'er</u>	sistent Organic Pollutants
Rotterdam Convention on P Not listed.	<u>ric</u>	<u>r Informed Consent (PIC)</u>
UNECE Aarhus Protocol on	PC)Ps and Heavy Metals
Not listed.		
Inventory list		
Australia		All components are listed or exempted.
Canada		All components are listed or exempted.
China		All components are listed or exempted.
Eurasian Economic Union		
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	All components are listed or exempted.
Philippines	:	All components are listed or exempted.
Republic of Korea	:	All components are listed or exempted.
Taiwan	:	All components are listed or exempted.
Thailand	:	Not determined.
Turkey	:	All components are listed or exempted.
United States of America	:	All components are active or exempted.
Viet Nam	÷	All components are listed or exempted.
15.2 Chemical Safety Assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

SECTION 16: Othe	er information
Abbreviations and	: 🗚 DN = European Provisions concerning the International Carriage of Dangerous
acronyms	Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of
	Dangerous Goods by Road
	ASTM = American Society for Testing and Materials
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DIN = German Institute for Standardization
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EC = European Commission
	EC50 = Half maximal effective concentration
	EN = European Standard (Norm)
	EUH statement = CLP-specific Hazard statement
	GHS - Globally Harmonized System of Classification and Labeling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IC50 = Half maximal inhibitory concentration
	IMDG = International Maritime Dangerous Goods
	IMO = International Maritime Organisation
	ISO = International Organization for Standardization
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
	NOEL / NOEC = No Observed Effect Level / Concentration
	OECD = Organisation for Economic Co-operation and Development
	OEL = Occupational Exposure Limit
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	Regulation [Regulation (EC) No. 1907/2006]
	RID = The Regulations concerning the International Carriage of Dangerous Good
	by Rail
	SDS = Safety Data Sheet
	SVHC = Substances of Very High Concern
	STEL = Short Term Exposure Limit
	TLV = Threshold Limit Value
	TWA = Time Weighted Average
	UFI = Unique Formula Identifier
	UN = United Nations
	VOC = Volatile Organic Compound
	vPvB = Very Persistent and Very Bioaccumulative
ocedure used to derive	e the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H332	Calculation method
Asp. Tox. 1, H304	Calculation method

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of abbreviated H statements

SECTION 16: Other information Highly flammable liquid and vapor. H225 H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. May cause an allergic skin reaction. H317 Causes serious eye damage. H318 Harmful if inhaled. H332 May cause respiratory irritation. H335 Harmful to aquatic life with long lasting effects. H412

Full text of classifications [CLP/GHS]

Acute Tox. 4 Aquatic Chronic 3	ACUTE TOXICITY - Category 4 AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 21-06-2023
Date of issue/ Date of	: 21-06-2023
revision	
Date of previous issue	e : 17-10-2020
Version	: 1.01
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands
Notice to reader	

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.