

Q8 Cylinder Oil C 460

Steam cylinder oil

Description

Q8 Cylinder Oil C is a steam cylinder oil with an optimum protection against wear and an excellent lubricity under wet conditions. This oil has high oxidation stability, natural resistance to gum formation and good film strength under steam washing conditions. Q8 Cylinder Oil C has an advanced adhesion to cylinder walls and water separation properties.

Applications

Q8 Cylinder Oil C is recommended for steam cylinders working under high temperatures and high pressure conditions. It is also applied in closed gears operating at low speed.

Features

Safety

Benefits

Tailored to the specific needs of your equipment to ensure safe and reliable operations

Enhanced technology

Excellent air release properties, outstanding anti-foaming performance and rapid water separation to ensure problem-free service.

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 20 °C	D 4052	g/ml	0,899
ISO Viscosity Grade	-	-	460
Kinematic Viscosity, 40 °C	D 445	mm ² /s	460
Kinematic Viscosity, 100 °C	D 445	mm ² /s	31.5
Viscosity Index	D 2270	-	100
Pour Point	D 97	°C	-15
Flash Point, COC	D 92	°C	314

The figures above are not a specification. They are typical figures obtained within production tolerances.