

Germ-Allcard Tantaroll XS - Product Range

Extreme heavy-duty stainless steel and alloyed steel drawing lubricant

Description

Tantaroll XS is a superior drawing fluid for heavy-duty applications of stainless steel and alloyed steel with medium to fine wire sizes. The product is based on medium viscosity exceptional quality base fluids and contains synthetic lubricity improvers, allowing for high drawing speeds. The active extreme pressure additives guarantee outstanding die life and the excellent oxidation stability ensures cleaner machines by avoiding lacquers and sticky deposits.

Applications

The Tantaroll XS range is formulated specifically for the heavy duty drawing of stainless steel and alloy steel.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from frost and direct sunlight, with bung holes horizontal to minimise breathing.

To optimise performance the following periodic checks are recommended: water ingress, viscosity increase, acidity and solids by filtration. Avoid operating at bulk temperatures in excess of 55°C.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Fluid type	-	-	___XS 16___ \ ___XS 24___ \ ___XS 42___
Kinematic Viscosity, 40 °C	D 445	mm ² /s	___16___ \ ___24___ \ ___41___
Density, 15 °C	D 4052	g/ml	___0.86___ \ ___0.87___ \ ___0.87___
Copper Strip, 3 h, 100 °C	D 130	-	___4___ \ ___4___ \ ___4___
Flash Point, COC	D 92	°C	___145___ \ ___205___ \ ___210___
Four Ball Test, Weld Load	IP 239	kg	___> 770___ \ ___> 770___ \ ___> 770___

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.