## PRODUCT DATA SHEET

# Q8 Bach 7530

High performance neat cutting oil with an advanced safety profile and low volatility

## **Description**

Q8 Bach 7530 is a medium viscosity, chlorine-free, lubricating oil with an active type of extreme pressure technology. This high performance cutting oil is based on the latest technology of high purity synthetic base fluids obtained chemically from natural gas, which are free from polycyclic aromatic compounds (PAH and BaP). Q8Bach 7530 has a high flash point and advanced safety profile. The low volatility results in lower consumption and provides a safer and healthier working environment.

## **Applications**

Q8 Bach 7530 is particularly developed for heavy duty cutting, and can also be used in broaching and general machining on hard materials

#### User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from frost and direct sunlight.

# Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

### **Properties**

|                            | Method | Unit  | Typical        |  |
|----------------------------|--------|-------|----------------|--|
| Density, 20 °C             | D 4052 | g/ml  | 0,837          |  |
| Kinematic Viscosity, 40 °C | D 445  | mm²/s | 33             |  |
| Appearance                 | Visual | -     | Bright & Clear |  |
| Copper Strip, 3 h, 100 °C  | D 130  | -     | 4              |  |
| Flash Point, COC           | D 92   | °C    | 200            |  |
| Four Ball Test, Weld Load  | IP 239 | kg    | > 800          |  |

The figures above are not a specification. They are typical figures obtained within production tolerances.

#### Remarks

Please contact your Q80ils representative for further advice and support on your specific application and equipment.