

Q8 Bernoulli S 54

Superior synthetic high temperature chain oil

Description

Q8 Bernoulli S 54 is an extreme fully synthetic high performance chain oil. It is designed for lubrication of high temperature chains and conveyor systems running at maximum 260°C. Q8 Bernoulli S 54 offers considerable energy savings, thanks to an exceptional additive technology, low evaporation losses, low friction coefficient and a reduced carbon build-up.

Applications

Q8 Bernoulli S oils are recommended for lubrication of conveyor systems running at a maximum temperature of 260°C. These conveyor systems are used in paint and drying ovens, textile stenters, gypsum drying ovens, glass insulation manufacturing and film stretching lines. Q8 Bernoulli S is also used in individual section glass forming machines for the production of glass containers and bottles.

Benefits

- Enhanced efficiency of operations, equipment and machines
- Extends service life time thus minimal costs and maximal efficiency
- Decreased downtime thanks to increased maintenance efficiency
- Superior decrease of friction
- Excellent additive technology
- Minimal evaporation losses
- Exceptional thermal durability
- Extremely resistant against high temperatures
- Superior cleaning properties
- Extreme adhesive characteristics
- Outstanding reduction of wear under boundary lubrication conditions

Properties

	Method	Unit	Typical
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	0,973
Kinematic Viscosity, 40 °C	D 445	mm ² /s	54
Kinematic Viscosity, 100 °C	D 445	mm ² /s	8.0
Viscosity Index	D 2270	-	117
Pour Point	D 97	°C	-42
Flash Point, COC	D 92	°C	>260
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Q8 Bernoulli S oils are silicone free. For woodpanel production, we suggest the Q8 Bernoulli S 280.