

Q8 Formula Techno Eco 0W-30

Synthetic ACEA C2 2021 and Ford WSS M2C-950A passenger car engine oil

Description

Q8 Formula Techno Eco 0W-30 is a synthetic, superior performance passenger car engine oil. Low in SAPS, this lubricant protects the aftertreatment systems and offers exceptional wear protection, engine cleanliness and fuel consumption reduction. It is biofuel compatible and is especially developed for the latest Ford cars requiring Ford WSS-M2C-950A.

Applications

Q8 Formula Techno Eco 0W-30 is designed for the latest Ford engines requiring Ford WSS-M2C-950A and ACEA C2 2021. This lubricant is also recommended for Fiat, Landrover and Jaguar.

Benefits

- Fuel economy improvement of 2,5% or more
- Best-in-class wear prevention ensuring long engine life.
- Superior aftertreatment system protection.
- Superior Bio-diesel compatibility due to improved oxidation stability.

Specifications, recommendations and approvals

ACEA	C2	Ford	M2C950-A
Fiat	9.55535-DS1	Jaguar Land Rover	STJLR.03.5007
Fiat	9.55535-GS1		

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0,843
Density, 15 °C	D 4052	g/ml	0,847
Viscosity Grade	-	-	SAE 0W-30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	45.2
Kinematic Viscosity, 100 °C	D 445	mm ² /s	9.4
Viscosity Index	D 2270	-	192
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>-2.9
Apparent Viscosity, -35 °C	D 5293	mPa.s	4900
Pour Point	D 97	°C	-48
Flash Point, COC	D 92	°C	220

The figures above are not a specification. They are typical figures obtained within production tolerances.