

## Q8 Holst AP 46

Advanced oil leak detecting zinc-free hydraulic oil

### Description

Q8 Holst AP 46 comes with a refreshing pine fragrance. This characteristic enables an easy and rapid detection of oil leakages in the hydraulic system. The Q8 Holst AP 46 is reliable for sensitive hydraulic servo systems thanks to its outstanding filterability and demulsibility. Because the oil has an excellent thermal and oxidation stability, it guarantees a long lubricant life time.

### Applications

Q8 Holst AP 46 is ideal for general hydraulic applications. It is also used in other industrial applications such as low charged gears, pumps, compressors and bearings. Thanks to its excellent filterability and demulsibility it is perfect for sensitive hydraulic servo systems. Q8 Holst AP 46 provides highest performance in systems sensitive to environmental contaminants.

### Benefits

- Easy and fast detection of oil leakages in the hydraulic system
- Minimizes downtime which leads to a higher maintenance efficiency
- Contains pine fragrance
- Highly user-friendly
- Zinc-free additives
- Optimum wear protection
- Highly resistant to oil deterioration

### Specifications & Approvals

DIN 51524-2 HLP ISO 11158 HM

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	0,874
Colour	D 1500	-	L 0.5
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	46
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	6.77
Viscosity Index	D 2270	-	98
Total Acid Number	D 974	mg KOH/g	0.10
Pour Point	D 97	°C	-27
Flash Point, COC	D 92	°C	218
Air Release, 50 °C	D 3427	min	3
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0 (10)
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
FZG Test, A/8.3/90	DIN 51354	load stage	>12

The figures above are not a specification. They are typical figures obtained within production tolerances.