

## Q8 Holst CR 15

Exceptional hydraulic oil for cold rolling mills

### Description

Q8 Holst CR 15 is a superior non-staining, zinc-free and ashless low viscosity hydraulic oil. It contains specially selected additives that offer exceptional equipment lubrication and that are compatible with all Q8Oils rolling oils. Q8 Holst CR 15 offers an extreme filterability and demulsibility. In case of leakages, the high performing low viscosity oil prevents loss of surface quality.

### Applications

Q8 Holst CR 15 is used in high pressure hydraulic systems in all types of cold rolling mills. It is also applied in sensitive hydraulic servo systems that require exceptional demulsibility and filterability.

### Benefits

- Minimizes downtime which leads to a higher maintenance efficiency
- Outstanding miscibility with other oils
- Superior oxidation stability
- Excellent thermal durability

### Specifications & Approvals

<b>Bosch Rexroth</b>	RE 90220 notes	<b>ISO</b>	11158 HM
<b>DIN</b>	51524-2 HLP		

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	15
Density, 15 °C	D 4052	g/ml	0,866
Colour	D 1500	-	L 0.5
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	16.5
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	3.6
Viscosity Index	D 2270	-	96
Pour Point	D 97	°C	-48
Flash Point, COC	D 92	°C	180
Air Release, 50 °C	D 3427	min	1
Emulsion, Distilled Water, 54.4 °C	D 1401	-	40-40-0 (10 min)
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	20/20/20
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0/0/0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1a
FZG Test, A/8.3/90	DIN 51354	load stage	11

The figures above are not a specification. They are typical figures obtained within production tolerances.