

Q8 Mahler MA SAE 40

Advanced stationary gas engine oil

Description

Q8 Mahler MA is an advanced gas engine oil, based on premium Group II (hydrotreated) base fluid. This product is designed as part of the Q8Oils gas engine oil technology program, which benefits from in-house developments and customized solutions.

Applications

Engine Lean-burn and stoichiometric four-stroke stationary gas engines, including high BMEP type. Operations Mild to severe conditions, including high pressure, high load and high temperature operations. Gas type Natural gas, also suitably for special gases requiring a low ash gas engine oil.

Features

Extended drain

Own product development

Enhanced technology

Benefits

Advanced alkalinity reserve maintains engine performance and durability while extending oil drain interval

In-house developed advanced additive package in combination with a carefully chosen Group II base oil

High lubricity properties providing low wear of engine components, significantly reducing maintenance costs

Specifications & Approvals

Caterpillar Energy Solutions	CG132, CG170, CG260	MTU Onsite Energy	400 series
Deutz	0199-99-01213	MWM	0199-99-02105
INNIO Waukesha	12-1880	Perkins	4006, 4008 series
MAN	M 3271-2 (Natural gas)		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,891
Viscosity Grade	-	-	SAE 40
Kinematic Viscosity, 40 °C	D 445	mm ² /s	115.8
Kinematic Viscosity, 100 °C	D 445	mm ² /s	13.05
Viscosity Index	D 2270	-	107
Total Base Number	D 2896	mg KOH/g	5.5
Pour Point	ASTM D 5950	°C	-21
Flash Point, P-M	D 93	°C	254
Sulfated Ash	D 874	% mass	0.5
Copper Strip, 3 h, 100 °C	D 130	-	1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

The original manufacturers recommendation should be followed.