

## Q8 SL Gear Lubricant 680

Exceptional performance oil for shock loaded industrial gears

### Description

Q8 SL Gear 680 is an exceptional performance oil specially developed for shock load conditions and operations in extremely harsh conditions. This oil has a superior wear protection in the most severe situations and has a Timken load performance of 290 N. Q8 SL Gear 680 meets the requirements of a major steel company and is oxidation resistant and thermal degraded.

### Applications

Q8 SL Gear 680 is perfect for extremely loaded and shock loaded industrial gearboxes operating in harsh conditions. used in steel, cement and mining industry. Q8 SL Gear 680 is perfect for extremely loaded and shock loaded industrial gearboxes operating in harsh conditions. Q8 SL Gear 680 can be used in damaged, worn or poorly aligned gear transmissions.

### Benefits

- Lower downtime and an improved maintenance efficiency
- Extends service life time thus minimal costs and maximal efficiency
- Extreme high load carrying capacity
- Extremely applicable in difficult and severe conditions
- Highly resistant to ageing
- Outstanding anti-rust properties

### Specifications & Approvals

ANSI/AGMA

9005-D94

ISO

12925-1 CKB-CKC-CKE

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	680
Density, 15 °C	D 4052	g/ml	0.911
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	682
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	38.2
Viscosity Index	D 2270	-	92
Flash Point, COC	D 92	°C	204
Foam, 5 min blowing, seq. 1-2-3	D 892	ml	0-0-0
Foam, 10 min settling, seq. 1-2-3	D 892	ml	0-0-0
Rust Test, Proc. A and B, 24 h	D 665	-	pass
Copper Strip, 3 h, 100 °C	D 130	-	1A
Four Ball Test, Weld Load	IP 239	N	5300
Timken, OK Load	D 2782	N	290
FZG Test, A/8.3/90	DIN 51354	load stage	>12

The figures above are not a specification. They are typical figures obtained within production tolerances.