

Q8 Stravinsky AB 100

Synthetic refrigeration compressor oil

Description

Q8 Stravinsky AB 100 is a synthetic refrigeration compressor oil developed with AB (AlkylBenzene) base fluid. The product is recommended for use with CFC-, HCFC- or traditional type refrigerant (such as ammonia). The outstanding thermal and oxidative stability provide extended and problem-free service life.

Applications

Reciprocating- and rotary refrigerator compressors Refrigerators, air conditioners, freezers and heat pumps Refrigerating systems handling CFC-, HCFC- or traditional type refrigerant (such as ammonia)

| Features Enhanced technology | Benefits Outstanding deposit control to keep the compressor clean, even under severe conditions |
|------------------------------|---|
| Extended drain | Extended oxidative stability, guaranteeing long oil life under continuous and severe operating conditions |
| Safety | Tailored to the specific needs of your equipment to ensure safe and reliable operations |

Properties

| | Method | Unit | Typical | |
|----------------------------|-------------|----------|------------|--|
| Appearance | Visual | - | ISO VG 100 | |
| Density, 15 °C | D 4052 | g/ml | 0,87 | |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 100 | |
| Pour Point | D 97 | °C | -27 | |
| Flash Point, COC | D 92 | °C | 195 | |
| Colour | D 1500 | - | L 0.5 | |
| R12 flocculant point | AMS. 100.42 | °C | < 60 | |
| Total Acid Number | D 974 | mg KOH/g | 0,02 | |
| Water content | D 1744 | ppm | 25 | |
| Copper Strip, 3 h, 100 °C | D 130 | - | 1 | |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky AB, it is recommended to flush the compressor lubricant system.