

## Q8 Stravinsky N 46

High performance refrigeration compressor oil

### Description

Q8 Stravinsky N 46 is a high performance refrigeration compressor oil. It is developed with premium selected naphtenic base fluid. The product is recommended for use with CFC-, HCFC- or traditional type refrigerant (such as ammonia). The low pour point and outstanding fluidity at low temperature ensure problem-free operations.

### Applications

Reciprocating- and rotary refrigerator compressors Industrial applications such as refrigerators and freezers Refrigerating systems handling CFC-, HCFC- or traditional type refrigerant (such as ammonia)

### Features

**Enhanced technology**

### Benefits

Fully compatible with mineral oils and normally used elastomer/plastic materials in compressor equipment

**Extended drain**

Advanced oxidative stability, guaranteeing long oil life under continuous and severe operating conditions

**Safety**

Tailored to the specific needs of your equipment to ensure safe and reliable operations

### Properties

	Method	Unit	Typical
ISO Viscosity Grade	-	-	46
Density, 15 °C	D 4052	g/ml	909
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	46.0
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	5.6
Flash Point, COC	D 92	°C	190

The figures above are not a specification. They are typical figures obtained within production tolerances.

### Remarks

Prior to the change of existing equipment from mineral oils or synthetic lubricants to Q8 Stravinsky N, it is recommended to flush the compressor lubricant system.