

Q8 da Vinci 6

Light demoulding oil with exceptional surface finishing

Description

Q8 da Vinci 6 is a superior demoulding oil with anti-rust inhibitors for steel moulds. It's solvent free and easily applicable. The reactive layer in the oil creates a layer between the concrete and the mould and contains additives for a clean demoulding. Q8Oils claims that Q8 da Vinci provides an exceptional smooth surface finish of the concrete and a clean mould without staining or dust.

Applications

Q8 da Vinci 6 is used for demoulding concrete foundation piles, tiles and on-site elements such as floors, stairs, balconies and prefab sewage pipes. It is applied in steel and plywood moulds. Q8 da Vinci 6 is highly recommended on site building constructions for direct release demoulding.

Benefits

- Leads to an improved durability of the finished product quality
- Outstanding quality of the surface
- Extremely effective demoulding operation
- Light colour
- Exceptional anti-rust properties
- Enhanced with special additives
- Prevents sticking
- Extremely handy to apply

Properties

| | Method | Unit | Typical |
|--------------------------------|--------|--------------------|------------------|
| Appearance | Visual | - | Bright and Clear |
| Density, 15 °C | D 4052 | g/ml | 0,836 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 6.0 |
| Pour Point | D 97 | °C | -21 |
| Flash Point, COC | D 92 | °C | 130 |
| Rust Test, Proc. A and B, 24 h | D 665 | - | pass |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

For use in cold temperatures, we recommend Q8 da Vinci P series. Q8 da Vinci range should be applied evenly and sparingly by low-pressure spray or brush onto a dry surface, ideally immediately after stripping. A second coat may be necessary when used on new timber or untreated wood.