

Q8 Allroads 2T

Synthetic based motorcycle fluid

Description

Q8 Allroads 2T is an excellent low smoke, pre-diluted, synthetic-based lubricant with an outstanding performance. It surpasses the most advanced international specifications and is recommended in a wide range of working conditions. Q8 Allroads 2T has outstanding cleaning and protection properties thanks to its balanced formulation based on low ash technology.

Applications

Q8 Allroads 2T is used for 2-stroke engines in on- and off-road motorcycles and modern scooters both with a premix lubrication system or an oil injection system for engines requesting specifications ISO, API, JASO and TISI.

Benefits

- Outstanding bearing lubrication and cylinder wear protection.
- Excellent low smoke characteristics at engine start and under traffic conditions.
- Outstanding protection against piston ring sticking and exhaust system blockage.
- Excellent low temperature fluidity.
- Outstanding protection against spark plug fouling and pre-ignition.

Specifications, recommendations and approvals

API	TC ++	JASO	FD
ISO	L-EGC	TISI	1040

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Kin. Viscosity Base Oil at 40 °C	D 445	mm ² /s	47,4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7,9
Viscosity Index	D 2270	-	138
Flash Point, P-M	D 93	°C	92
Pour Point	D 97	°C	-24
Sulfated Ash	D 874	% mass	0.1
Colour	Visual	-	Red
Total Base Number	D 2896	mg KOH/g	2.3

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

It is advisable to adopt a concentration that complies with the requirements of the engine manufacturer.