

Q8 Auto 15 V

Full synthetic automatic transmission fluid with extended drain capability

Description

Q8 Auto 15 V is a superior performance full synthetic automatic transmission fluid, designed for heavy duty vehicles. The product is especially formulated for trucks, buses and military equipment in severe operating conditions.

Applications

Q8 Auto 15 V is developed for severe operating conditions. It is specifically designed for Voith DIWA Transmissions requiring Voith ATF specification Voith 150.014524.xx, offering up to 180.000 km drain interval. The product is also recommended for ZF, MAN, Volvo and Mercedes-Benz.

Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

| | | | |
|-------------------------|------------------------|--------------|----------------------|
| Daimler Truck AG | DTFR 13C170 (MB 236.9) | Voith | US SB 013/118 |
| MAN | 339 Type V2 | Volvo | 97341 (AT 101) |
| MAN | 339 Type Z12 | ZF | TE-ML 14C |
| MAN | 339 Type Z3 | ZF | TE-ML 20C |
| Voith | 150.014524.xx | | |

Color code blue = officially approved

Properties

| | Method | Unit | Typical |
|------------------------------|--------|--------------------|---------|
| Density, 15 °C | D 4052 | g/ml | 0,85 |
| Kinematic Viscosity, 40 °C | D 445 | mm ² /s | 40 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 7.35 |
| Viscosity Index | D 2270 | - | 151 |
| Brookfield Viscosity, -40 °C | D 2983 | Pa.s | 12.0 |
| Pour Point | D 97 | °C | -45 |
| Flash Point, COC | D 92 | °C | >200 |

The figures above are not a specification. They are typical figures obtained within production tolerances.