

Q8 T 520 SAE 30

Mineral API CG-4 heavy-duty engine oil

Description

Q8 T 520 SAE 30 is a heavy-duty engine oil formulated to suit the needs of old generation vehicles with turbocharged engines. The oil has been formulated with a special package of additives and detergents/dispersants. It provides advanced anti-wear capacity, optimum lubrication and keeps the engine clean.

Applications

Q8 T 520 SAE 30 can be used as engine or transmission lubricant in commercial vehicles, buses, off-highway/construction or military equipment. It's developed for old generation vehicles having turbocharged engines. To be used where monograde engine oil is preferred

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.

Specifications, recommendations and approvals

API	CG-4	MB	227.0
Allison	C-3	MB	228.0
Caterpillar	TO-2	MTU	Type 1
Caterpillar	TO-2	Voith	Retarder
MAN	M 270		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0.889
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	94
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.36
Viscosity Index	D 2270	-	108
Total Base Number	D 2896	mg KOH/g	8.5
Pour Point	D 97	°C	-21
Flash Point, P-M	D 93	°C	208
Sulfated Ash	D 874	% mass	1.1

The figures above are not a specification. They are typical figures obtained within production tolerances.