

Q8 T 750 SAE 10W

Mineral API CI-4 and ACEA E7 heavy duty engine oil

Description

Q8 T 750 SAE 10W is a heavy duty engine oil. This product is designed to improve engine durability and to prevent deposit formation. It prevents corrosion and foaming. It meets the requirements of API CI-4 ACEA E7.

Applications

Q8 T 750 SAE 10W for commercial vehicles, buses, off-highway/construction or military equipment. To be used where monograde engine oil is preferred in some transmission applications. Can be used in hydraulic systems requiring ISO VG 32 or 46.

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

ACEA	A3/B4	API	SL
ACEA	E3	MTU	Type 1
ACEA	E5	NATO	O-237
ACEA	E7	NATO	O-237
API	CI-4		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,893
Viscosity Grade	-	-	SAE 10W
Kinematic Viscosity, 40 °C	D 445	mm ² /s	47.7
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.42
Viscosity Index	D 2270	-	118
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-42
Flash Point, P-M	D 93	°C	204
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.