

Q8 T 750 SAE 30

Heavy-duty engine oil ACEA E7 and API CI-4.

Description

Q8 T 750 SAE 30 is an advanced heavy-duty engine oil. It provides good lubrication, limits wear, prohibits corrosion and protects against rust.

Applications

Q8 T 750 SAE 30 can be used as diesel engine or transmission lubricant in commercial vehicles, buses, off-highway/construction and military equipment. It's developed for engines normally aspirated, turbocharged or supercharged, with or without intercooling and Tier 3 engine technology. To be used where monograde engine oil is preferred

Benefits

- Premium protection against engine wear.
- High protection against rust and corrosion.
- Advanced engine protection after cold start.

Specifications, recommendations and approvals

ACEA	A3/B4	MAN	M 270
ACEA	E3	MB	227.0
ACEA	E5	MB	228.0
ACEA	E7	MTU	Type 1
API	CI-4	MTU	Type 2
API	SL	Voith	Retarder
Caterpillar	TO-2		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,889
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	90.5
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.2
Viscosity Index	D 2270	-	109
Total Base Number	D 2896	mg KOH/g	10
Pour Point	D 97	°C	-27
Flash Point, P-M	D 93	°C	206
Sulfated Ash	D 874	% mass	1.3

The figures above are not a specification. They are typical figures obtained within production tolerances.