

Q8 Unishift PC Synt 75W

Synthetic API GL-4 manual transmission fluid

Description

Q8 Unishift PC Synt 75W is a superior manual transmission fluid for passenger cars and light duty vehicles. This versatile lubricant offers exceptional protection and durability, even under extreme pressure, and provides best-in-class thermal stability, making it suitable for a wide variety of passenger car applications. It meets the requirements of most OEMs based on API GL-4.

Applications

Q8 Unishift PC Synt 75W is a versatile lubricant designed to be used in passenger cars and light duty synchromesh manual gearboxes and transaxles, specifically in high load carrying situations. It meets the API GL-4 specification and the requirements of most European and Asian manufacturers.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Excellent easy gear shifting at low temperatures.
- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

API	GL-4	PSA	9730-A8
BMW/MINI	JWS 2271	PSA	B71 2310
BMW/MINI	MTF-LT2	VAG	VW G 052 171
BMW/MINI	MTF-LT3	VAG	VW G 052 512
Fiat	9.55550-MZ14	VAG	VW G 052 527
Fiat	9.55550-MZ2	VAG	VW G 052 527
Fiat	9.55550-MZ27	VAG	VW G 052 549
Fiat	9.55550-MZ6	VAG	VW G 052 798
Ford	M2C200-D1	VAG	VW G 52 726
Ford	M2C200-D2	VAG	VW TL 521 71 (G 052 171 A1/A2)
GM	MTF 0063	VAG	VW TL 521 78 (G 052 178 A2)
MB	235.71	VAG	VW TL 525 12 (G 052 512 A2)

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,847
Viscosity Grade	-	-	SAE 75W
Kinematic Viscosity, 40 °C	D 445	mm ² /s	33
Kinematic Viscosity, 100 °C	D 445	mm ² /s	6.8
Viscosity Index	D 2270	-	172
Brookfield Viscosity, -40 °C	D 2983	Pa.s	44
Pour Point	D 97	°C	-39
Flash Point, P-M	D 93	°C	195

The figures above are not a specification. They are typical figures obtained within production tolerances.