

Q8 City 4T 10W-30

Advanced motorcycle oil for city traffic conditions

Description

Q8 City 4T 10W-30 is an advanced synthetic motorcycle oil that protects the critical engine parts while driving in city traffic. The oil contains special additives to guarantee a high protection of engine and transmission parts and to assure a strong oxidation stability. Q8 City 4T 10W-30 provides optimum friction in the wet clutch and has advanced antioxidation properties.

Applications

Q8 City 4T 10W-30 is used for motorcycles and scooters in city traffic. It is suitable for all types of four stroke motorcycles where JASO MA2 performance is recommended.

Benefits

- Excellent cylinder protection against scuffing wear.
- Outstanding environmental impact reduction.
- Outstanding clutch friction performance.
- Excellent high temperature control.
- Excellent protection against rust and corrosion.

Specifications, recommendations and approvals

API SL JASO MA2

Properties

| | Method | Unit | Typical |
|----------------------------------|--------|--------------------|---------|
| Density, 15 °C | D 4052 | g/ml | 0,850 |
| Density, 20 °C | D 4052 | g/ml | 0,847 |
| Viscosity Grade | - | - | 10W-30 |
| Kin. Viscosity Base Oil at 40 °C | D 445 | mm ² /s | 56,7 |
| Kinematic Viscosity, 100 °C | D 445 | mm ² /s | 9,8 |
| Viscosity Index | D 2270 | - | 159 |
| Pour Point | D 97 | °C | -33 |
| Flash Point, COC | D 92 | °C | 235 |

The figures above are not a specification. They are typical figures obtained within production tolerances.