

Q8 Formula Hybrid GF-6A 0W-20

Synthetic engine oil for hybrid cars

Description

Q8 Formula Hybrid GF-6A 0W-20 is a synthetic superior performance passenger car engine oil for hybrid cars. This lubricant provides fuel economy up to 2,9% and extended drain intervals. It ensures best-in-class engine cleanliness which increases the durability of the engine. It is fully compatible with bio fuel.

Applications

Q8 Formula Hybrid GF-6A 0W-20 is a synthetic superior performance passenger car engine oil for hybrid cars requiring API SP RC, API SP, API SN Plus RC, SN Plus, SN and ILSAC GF-6A, GF-5

Benefits

- Improved fuel economy.
- Exceptional engine protection after cold starting.
- Superior oil film strength preventing engine wear.
- Superior oxidation stability
- Best-in-class wear prevention ensuring long engine life.

Specifications, recommendations and approvals

| API | SN | API | SP |
|-----|------------|-------|-------|
| API | SN Plus | API | SP-RC |
| API | SN Plus-RC | ILSAC | GF-5 |
| API | SN-RC | ILSAC | GF-6A |

Properties

| | Method | Unit | Typical |
|-----------------------------|--------|---------|---------|
| Density, 15 °C | D 4052 | g/ml | 0,848 |
| Density, 20 °C | D 4052 | g/ml | 0,845 |
| Viscosity Grade | - | - | 0W-20 |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 42 |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 8,1 |
| Viscosity Index | D 2270 | - | 171 |
| Apparent Viscosity, -35 °C | D 5293 | mPa.s | 6000 |
| Pour Point | D 97 | °C | -46 |
| Flash Point, COC | D 92 | °C (°F) | 210 |
| Sulfated Ash | D 874 | % mass | 0,9 |

The figures above are not a specification. They are typical figures obtained within production tolerances.