

Q8 T 40 75W-90

Synthetic API GL-4 transmission fluid

Description

Q8 T 40 75W-90 is an outstanding synthetic manual transmission fluid for 4 or 5 speed passenger cars and vans. This product delivers easy gear shifting, even at low temperatures. It provides superb protection against wear, corrosion and rust.

Applications

Q8 T 40 75W-90 is developed for passenger cars and vans that require the API GL-4 specification.

Benefits

- Outstanding protection against wear and extends component life.
- Excellent easy gear shifting at low temperatures.
- Outstanding protection against rust and corrosion.
- Reduces drive-line operating temperatures.

Specifications, recommendations and approvals

API	GL-4	Ford	M2C200-C
Fiat	9.55550-MX3	Ford	SQM-2C9008-A
Fiat	9.55550-MZ1	Mazda	
Fiat	9.55550-MZ11	Mitsubishi	
Fiat	9.55550-MZ3	ZF	Synchromesh transmissions
Fiat	9.55550-MZ4		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,85
Viscosity Grade	-	-	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm ² /s	89,4
Kinematic Viscosity, 100 °C	D 445	mm ² /s	14,3
Viscosity Index	D 2270	-	166
Brookfield Viscosity, -40 °C	D 2983	Pa.s	64,2
Pour Point	D 97	°C	-42
Flash Point, P-M	D 93	°C	202

The figures above are not a specification. They are typical figures obtained within production tolerances.