

Q8 Formula F1 10W-60

Synthetic passenger car engine oil for racing conditions

Description

Q8 Formula F1 10W-60 is a high-performing synthetic year round engine oil, designed for superior engine protection under intense driving conditions, particularly racing. The product is formulated to sustain high oil pressure and deliver excellent oil film strength to protect the engine from wear.

Applications

Q8 Formula F1 10W-60 is formulated for vehicles with normally aspirated or turbo charged gasoline or diesel engines. It is especially recommended for highest performance, multi-valve engines with a catalyst and high-performance sports cars. Recommended for Porsche naturally aspirated engines.

Benefits

- Exceptional engine performance in different driving conditions.
- Superior oil film strength preventing engine wear.
- Superior protection against rust and corrosion.
- Best-in-class wear prevention ensuring long engine life.

Specifications, recommendations and approvals

ACEA A3/B4 API SP

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,875
Viscosity Grade	-	-	SAE 10W-60
Kinematic Viscosity, 40 °C	D 445	mm²/s	162
Kinematic Viscosity, 100 °C	D 445	mm²/s	23.0
Viscosity Index	D 2270	-	171
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=5.5
Apparent Viscosity, -25 °C	D 5293	mPa.s	6600
Pour Point	D 97	°C	-24
Flash Point, P-M	D 93	°C	215
Borderline Pumpina Temperature	D 3829	°C	-27

The figures above are not a specification. They are typical figures obtained within production tolerances.