# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

# SAFETY DATA SHEET

# Q8 Verdi 5



SECTION 1: Identification of the substance/mixture and of the company/ undertaking			
1.1 Product identifier			
Product name	: Q8 Verdi 5		
Viscosity or Type	: ISO VG 5		
1.2 Relevant identified uses	of the substance or mixture and u	ises advised against	
Material uses	: Lubricating oil for industrial syst	ems	
1.3 Details of the supplier of	the safety data sheet		
Supplier	: Kuwait Petroleum Companies in Company Office: Brusselstraat Contactaddress: Petroleumkaa Tel. +32 3 247 38 11, Fax +32 3	59, 2018 Antwerp, Belgiur i 7, 2020 Antwerp, Belgiur	
Manufacturer / Distributor	: Kuwait Petroleum Belgium N.V. Petroleumkaai 7 B-2020 Antwerp Belgium	Via Volpedo	
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communica	tion preferably in English	only.
PCN Information contact	: PCNinfo@Q8.com, communica	tion preferably in English	only.
1.4 Emergency telephone nu	mber		
Europe	: +44 (0) 1235 239 670	CARECHEM24	
Global (English only)	: +44 (0) 1865 407 333	CAREONEWIZ4	
National advisory body/Poi	son Center		
Belgium	: Poison Centre : +32 (0)70 245	245	
SECTION 2: Hazards	identification		
2.1 Classification of the subs	stance or mixture		
Product definition	: Mixture		
	Regulation (EC) No. 1272/2008 [C		
ASPIRATION HAZARD	ERM)	Category 1 Category 3	H304 H412
The product is classified as h	azardous according to Regulation (I	EC) 1272/2008 as amende	ed.
Ingredients of unknown toxicity	: None.		
Ingredients of unknown ecotoxicity	: None.		

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

<b>SECTION 2: Hazards identifica</b>	ation
--------------------------------------	-------

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	;	H304 - May be fatal if swallowed and enters airways. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements		
Prevention	1	P273 - Avoid release to the environment.
Response	:	₱301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.
Storage	1	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	₩ydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics Distillates (petroleum), hydrotreated light paraffinic
Supplemental label elements	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Detergents - Regulation (EC) No 648/2004	:	Not applicable.
Special packaging requirem	<u>ier</u>	<u>Its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	In the provided a strain of the provided and the provided a pr
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture			<b>r</b>	
Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, <0.03% aromatics	REACH #: 01-2119827000-58 EC: 934-956-3 CAS: 1335203-17-2	≥75 - ≤90	Asp. Tox. 1, H304	-	[1] [2]
- · · · · · · · · · · · · · · /,	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	≥10 - ≤25	Asp. Tox. 1, H304	-	[1] [2]
Date of issue/Date of revision	:08-11-2022 Date	e of previous is	sue : 26-05-2017	Version : 1.0	)5 2/15

# **SECTION 3: Composition/information on ingredients**

•					
2,6-di-tert-butylphenol	REACH #: 01-2119490822-33 EC: 204-884-0 CAS: 128-39-2	<1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M [Acute] = 1 M [Chronic] = 1	[1]
Distillates (petroleum), hydrotreated light naphthenic	REACH #: 01-2119480375-34 EC: 265-156-6 CAS: 64742-53-6 Index: 649-466-00-2	≤0.1	Asp. Tox. 1, H304	-	[1] [2]
			See Section 16 for the full text of the H statements declared above.		

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section. <u>Type</u>

Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Set medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

<u>Over-exposure signs/symptoms</u>			
Eye contact	: No specific data.		
Inhalation	: No specific data.		

SECTION 4: First aid	1 measures
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: Adverse symptoms may include the following: nausea or vomiting
4.3 Indication of any immedi	iate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
<b>SECTION 5: Firefigh</b>	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	: Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

	-	
Hazards from the substance or mixture	•	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides
5.3 Advice for firefighters		
Special protective actions for fire-fighters	1	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

6.1 Personal precautions, pro	te	ctive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### SECTION 6: Accidental release measures

6.3 Methods and materials	s for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not swallow. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

### **Occupational exposure limits**

### SECTION 8: Exposure controls/personal protection

	1
Product/ingredient name	Exposure limit values
Hydrocarbons, C15-C20, n-alkanes, isoalkanes,	Limit values (Belgium, 5/2021). []
cyclics, <0.03% aromatics	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist
	EU OEL (Europe).
	TWA: 5 mg/m <sup>3</sup>
Distillates (petroleum), hydrotreated light	Limit values (Belgium, 12/2020).
paraffinic	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist
	EU OEL (Europe).
	TWA: 5 mg/m <sup>3</sup> 8 hours.
	STEL: 10 mg/m³ 15 minutes.
Distillates (petroleum), hydrotreated light	Limit values (Belgium, 12/2020).
naphthenic	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist
	STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist
	EU OEL (Europe).
	TWA: 5 mg/m³, (oil Mist)

Recommended monitoring procedures If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
₩ydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	DNEL	Long term Oral	1.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.25 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	2.91 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	4.85 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	16.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	3001.6 mg/ m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	5002.67 mg/m <sup>3</sup>	Workers	Systemic
2,6-di-tert-butylphenol	DNEL	Long term Oral	6.75 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	11.25 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	20.9 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	70.61 mg/ m³	Workers	Systemic
	DNEL	Long term Dermal	6.75 mg/ kg bw/day	General population	Systemic

#### **PNECs**

No PNECs available.

# Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

Q8 Verdi 5

### **SECTION 8: Exposure controls/personal protection**

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	r <mark>es</mark>
Hygiene measures	: Do not ingest. If swallowed then seek immediate medical assistance. Wash hands forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicate this is necessary. Considering the parameters specified by the glove manufacturer check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

	· · · · · · · · · · · · · · · · · · ·
Appearance	
Physical state	: Liquid. [Oily liquid.]
Appearance	: Clear.
Color	: Yellow [Light]
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing poi	nt : Not applicable.
Pour point	: 롣12°C (<10.4°F) [ASTM D 97]

SECTION 9: Physical and chemical properties					
Initial boiling point and boiling range	: >260°C (>500°F)				
Flammability	: Not applicable.				
Lower and upper explosion	: Not available.				

ż

limit	
Flash point	: Open cup: >130°C (>266°F) [ASTM D92.]
Auto-ignition temperature	: >230°C (>446°F)
Decomposition temperature	: >260°C
pH	: Not applicable.
Viscosity	: Kinematic (40°C (104°F)): 5 mm²/s (5 cSt) [ASTM D 445] Kinematic (100°C (212°F)): 1.67 mm²/s (1.67 cSt) [ASTM D 445]

### Solubility(ies)

Media	Result
cold water hot water	Not soluble Not soluble
Partition coefficient: n-octanol/ water	: Not applicable.
Vapor pressure	: 📈 0.01 kPa (<0.075006 mm Hg)
Density	: 🗭.82 g/cm³ [15°C (59°F)] [ASTM D 4052]
Vapor density	: Not available.
Explosive properties	: Not applicable.
Oxidizing properties	: Not applicable.
Particle characteristics	
Median particle size	: Not applicable.

#### **SECTION 10: Stability and reactivity 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients. **10.2 Chemical stability** : The product is stable. **10.3 Possibility of** : Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions 10.4 Conditions to avoid : No specific data. **10.5 Incompatible materials** : Reactive or incompatible with the following materials: Strong oxidizing materials **10.6 Hazardous** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. decomposition products

## **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

# **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
ydrocarbons, C15-C20, n- Ikanes, isoalkanes, cyclics, 0.03% aromatics	LC50 Inhalation Dusts and mists	Rat	>5266 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), ydrotreated light paraffinic	LC50 Inhalation Dusts and mists	Rat	3900 mg/m³	4 hours
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-
,6-di-tert-butylphenol	LD50 Dermal	Rabbit	>10 g/kg	-
	LD50 Oral	Rat	1320 mg/kg	-
Distillates (petroleum), ydrotreated light aphthenic	LC50 Inhalation Dusts and mists	Rat	2180 mg/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	>5000 mg/kg	-

Conclusion/Summary

Acute toxicity estimates

N/A

### Irritation/Corrosion

Product/ingredient name	Resu	lt	Species	Score	Exposure	Observation
♥istillates (petroleum), hydrotreated light paraffinic	Eyes - Iris lesion		Rabbit	0	48 hours	72 hours
	Eyes - Redness of	f the	Rabbit	0.33	48 hours	72 hours
	conjunctivae Skin - Edema		Rabbit	0	72 hours	7 days
	Skin - Erythema/E	schar	Rabbit	0.17	72 hours	7 days 7 days
2,6-di-tert-butylphenol	Skin - Moderate in		Rat	-	0.5 MI	-
Conclusion/Summary				•		
Skin	: Non-irritant to skin.					
Eyes	: Non-irritating to the eyes.					
Respiratory	: Non-irritant to lu	: Non-irritant to lungs.				
Sensitization						
Product/ingredient name	Route of exposure				Result	
₱istillates (petroleum), hydrotreated light paraffinic	skin	Guinea pig Not ser		ensitizing	isitizing	
Conclusion/Summary	· · · · · · · · · · · · · · · · · · ·			·		
Skin	: Not sensitizing					
Respiratory	: Not classified for respiratory sensitization.					
<u>Mutagenicity</u>						
Product/ingredient name	Test Experiment Result			Result		

Product/ingredient name	Test	Experiment	Result
₱istillates (petroleum), hydrotreated light paraffinic	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

**Conclusion/Summary** 

: No mutagenic effect.

#### **Carcinogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
₱istillates (petroleum), hydrotreated light paraffinic	Negative - Dermal - TC	Mouse - Female	-	78 weeks

## **SECTION 11:** Toxicological information

**Conclusion/Summary** : No carcinogenic effect.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
₱istillates (petroleum), hydrotreated light paraffinic	Negative	Negative	Negative	,	Oral: 1000 mg/ kg	-

#### **Conclusion/Summary**

: No known significant effects or critical hazards.

#### **Teratogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
₱istillates (petroleum), hydrotreated light paraffinic	Negative - Dermal	Rat	2000 mg/kg	7 days per week

#### **Conclusion/Summary** : No known significant effects or critical hazards.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Product/ingredient name	Result
▼ydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), hydrotreated light naphthenic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

#### Information on the likely : Not available. routes of exposure Potential acute health effects : No known significant effects or critical hazards. Eye contact Inhalation : No known significant effects or critical hazards. Skin contact : Defatting to the skin. May cause skin dryness and irritation. : May be fatal if swallowed and enters airways. Ingestion Symptoms related to the physical, chemical and toxicological characteristics Eye contact : No specific data. Inhalation : No specific data. Skin contact : Adverse symptoms may include the following: irritation dryness cracking Ingestion ÷. Adverse symptoms may include the following: nausea or vomiting Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure **Potential immediate** : Not available. effects Potential delayed effects : Not available. Long term exposure

# **SECTION 11: Toxicological information**

**Potential immediate** effects

: Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
♥istillates (petroleum), hydrotreated light paraffinic	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Dusts and mists	Rat - Male	>980 mg/m³	4 weeks; 5 days per week
Conclusion/Summary	: Not toxic.	-		
General	: Prolonged or repeated conta or dermatitis.	act can defat the	e skin and lead to irri	tation, cracking and/
Carcinogenicity	: No known significant effects	or critical hazar	ds.	
Mutagenicity	: No known significant effects	or critical hazar	ds.	
Bernard and the first state			. 1.	

**Reproductive toxicity** : No known significant effects or critical hazards.

#### 11.2 Information on other hazards

#### **11.2.1 Endocrine disrupting properties**

Not available.

11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
✓ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, <0.03% aromatics	Acute EC50 >10000 mg/l	Algae	72 hours
	Acute EC50 >3193 mg/l Acute EC50 >1028 mg/l	Daphnia Fish	48 hours 96 hours
Conclusion/Summary	: Not available.		L.

Conclusion/Summary

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose	Inoculum
₩ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, <0.03% aromatics	OECD 306	74 % - Readily - 28	days	-	-
Conclusion/Summary	: Not available.	•		-	
Product/ingredient name	Aquatic half-life		Photolysi	S	Biodegradability
ydrocarbons, C15-C20, n- alkanes, isoalkanes, cyclics, <0.03% aromatics	-		-		Readily
Distillates (petroleum), hydrotreated light paraffinic	-		-		Inherent

#### **12.3 Bioaccumulative potential**

# **SECTION 12: Ecological information**

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), hydrotreated light paraffinic	>3	-	low
2,6-di-tert-butylphenol	4.5	-	high

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### **12.6 Endocrine disrupting properties**

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 13.1 Waste treatment methods

#### Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
I lamanda ya waata	

Hazardous waste : Yes.

#### European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
Packaging	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **SECTION 14: Transport information**

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

```
14.6 Special precautions for user
```

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in** : Not available. bulk according to IMO instruments

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Other EU regulations	
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed
Ozone depleting substanc	<u>es (1005/2009/EU)</u>
Not listed.	
Prior Informed Consent (P Not listed.	<u>PIC) (649/2012/EU)</u>

# **SECTION 15: Regulatory information**

### Persistent Organic Pollutants

Not listed.

#### Seveso Directive

This product is not controlled under the Seveso Directive.

Hazard class for water : 🕅

(WGK)

VOC content : Exempt.

#### International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### **Montreal Protocol**

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

# Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

Assessment

#### Inventory list

Australia	1	Not determined.
Canada	:	Not determined.
China	:	Not determined.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): Not determined. Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	Not determined.
Republic of Korea	:	Not determined.
Taiwan	:	Not determined.
Thailand	:	Not determined.
Turkey	:	Not determined.
United States	:	Not determined.
Viet Nam	:	Not determined.
15.2 Chemical Safety	:	Chemical Safety Assessments for all substances in this product are either Complete

# **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

or Not applicable.

Abbreviations and acronyms	<ul> <li>ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Re 1272/2008]</li> <li>DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available</li> <li>PBT = Persistent, Bioaccumulative and Toxic</li> <li>PNEC = Predicted No Effect Concentration</li> <li>RRN = REACH Registration Number SGG = Segregation Group</li> </ul>	∋gulation (EC) No	
Date of issue/Date of revision	: 08-11-2022 Date of previous issue : 26-05-2017	Version : 1.05	14/15

### **SECTION 16: Other information**

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
	Calculation method Calculation method

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

#### Full text of abbreviated H statements

<b>⊮</b> 304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Full text of classifications [CLP/GHS]

Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 3 Asp. Tox. 1 Eye Irrit. 2 Skin Irrit. 2	AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 3 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 SKIN CORROSION/IRRITATION - Category 2
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 08-11-2022
Date of issue/ Date of revision	: 08-11-2022
Date of previous issue	e : 26-05-2017
Version	: 1.05
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands
Notice to reader	

#### Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.