

MA2

Q8 Allroads 4T 10W-40

Excellent synthetic motorcycle oil

Description

Q8 Allroads 4T 10W-40 is an excellent synthetic motorcycle oil that matches various driving conditions. Its robust formulation provides a strong film on all moving parts to guarantee an outstanding wear protection and gear pitting in all driving conditions. Q8 Allroads 4T 10W-40 exceeds the top international OEM requirements.

Applications

Q8 Allroads 4T 10W-40 is used in on-road motorcycles (daily transportation) and off-road motorcycles with dry or wet clutch. It is used in both air and water cooled engines.

Benefits

API

- Excellent engine performance at extreme driving conditions.
- Outstanding year round properties.
- Excellent protection against rust and corrosion.
- Outstanding bearing lubrication and cylinder wear protection.
- Excellent cleanliness and wear protection for all components.

Specifications, recommendations and approvals

SL

| Properties | | | |
|-----------------------------|--------|-------|---------|
| | Method | Unit | Typical |
| Density, 20 °C | D 4052 | g/ml | 0,861 |
| Density, 15 °C | D 4052 | g/ml | 0,864 |
| Viscosity Grade | - | - | 10W-40 |
| Kinematic Viscosity, 40 °C | D 445 | mm²/s | 98 |
| Kinematic Viscosity, 100 °C | D 445 | mm²/s | 14.3 |
| Viscosity Index | D 2270 | - | 150 |
| Pour Point | D 97 | °C | -39 |
| Flash Point, COC | D 92 | °C | 231 |

JASO

The figures above are not a specification. They are typical figures obtained within production tolerances.