

Q8 Auto 15 V

Full synthetic automatic transmission fluid with extended drain capability

Description

Q8 Auto 15 V is a superior performance full synthetic automatic transmission fluid, designed for heavy duty vehicles. The product is especially formulated for trucks, buses and military equipment in severe operating conditions.

Applications

Q8 Auto 15 V is developed for severe operating conditions. It is specifically designed for Voith DIWA Transmissions requiring Voith ATF specification Voith 150.014524.xx, offering up to 180.000 km drain interval. The product is also recommended for ZF, MAN, Volvo and Mercedes-Benz.

Benefits

- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

Daimler Truck AG	DTFR 13C170 (MB 236.9)	Voith	US SB 013/118
MAN	339 Type V2	Volvo	97341 (AT 101)
MAN	339 Type Z12	ZF	TE-ML 14C
MAN	339 Type Z3	ZF	TE-ML 20C
Voith	150.014524.xx		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,85
Kinematic Viscosity, 40 °C	D 445	mm ² /s	40
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.35
Viscosity Index	D 2270	-	151
Brookfield Viscosity, -40 °C	D 2983	Pa.s	12.0
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	>200

The figures above are not a specification. They are typical figures obtained within production tolerances.