

MA2

Q8 Racing 4T 10W-50

Superior motorcycle oil

Description

Q8 Racing 4T 10W-50 is a superior synthetic lubricant that enhances power performance of 4-stroke motorcycles. It contains a unique polymeric Viscosity Index improver and exceptional anti-wear additives that result in an extreme film strength. Q8 Racing 4T 10W-50 guarantees exceptional engine cleanliness, is mechanical and thermal stable and delivers non-stop peak performance in all conditions.

Applications

Q8 Racing 4T 10W-50 is used in on- and off-road motorcycles with dry and wet clutch. It is suitable for recreational devices such as all terrain vehicles (ATV) and quads. The oil exceeds the top international OEM requirements.

Benefits

API

Properties

- Excellent engine performance at extreme driving conditions.
- Excellent cleanliness and wear protection for all components.
- Excellent high temperature control.
- Excellent cylinder protection against scuffing wear.
- Excellent protection against rust and corrosion.

Specifications, recommendations and approvals

SN

Troperties				
	Method	Unit	Typical	
Density, 15 °C	D 4052	g/ml	0,857	
Viscosity Grade	-	-	10W-50	
Kinematic Viscosity, 40 °C	ISO 3104	mm²/s	121	
Kinematic Viscosity, 100 °C	D 445	mm²/s	18,2	
Viscosity Index	D 2270	-	172	
Flash Point, P-M	D 93	°C	220	
Pour Point	D 97	°C	-36	,

JASO

 $The \ figures \ above \ are \ not \ a \ specification. \ They \ are \ typical \ figures \ obtained \ within \ production \ tolerances.$