PRODUCT DATA SHEET

Q8 T 2300 CVT 10W-30

Exceptional synthetic Tractor Continuous Variable Transmission Fluid

Description

Q8 T 2300 CVT 10W-30 is an exceptional synthetic tractor fluid for continuous variable transmissions. It guarantees superior protection for off-highway, construction and agricultural equipment. The versatile Q8 T 2300 CVT 10W-30 achieves the latest performance credentials from API and several OEMs. It improves durability and enhances both operator comfort and productivity.

Applications

Q8 T 2300 CVT 10W-30 is used in continuous variable transmissions in off-highway, construction and agricultural applications such as tractors and harvesters. It is applied as driveline lubricant, oil immersed brake/clutch fluid, hydraulic fluid and transmission lubricant. The oil meets the requirements of almost all OEMs.

Benefits

- *Superior viscosity retention providing smoothless CVT operation.*
- *Best-in-class oxidation stability.*
- *Superior frictional properties for smooth brake operation.*
- *Superior response of hydraulic components.*
- *Maximum compatibility with conventional elastomers.*

Specifications, recommendations and approvals

AGCO	CVT ML 200	**Massey Ferguson**	CMS M 1143
API	GL-4	**Massey Ferguson**	CMS M 1145
Case	MS 1207	**New Holland**	NH 410-B
Case	MS 1209	**New Holland**	NH 410-C
Case	MS 1210	**Same Deutz Fahr**	UTTO
Case New Holland	MAT 3505	**Valtra**	G2-08 (XT-60)
Case New Holland	MAT 3525	**Valtra**	G2-B10 (XT-60+)
Case New Holland	MAT 3540	**ZF**	TE-ML 03E
Case New Holland	MAT 3544	**ZF**	TE-ML 05F
Case New Holland	MAT 3552-A	**ZF**	TE-ML 06B
Case New Holland	MAT 3553-A	**ZF**	TE-ML 06D
Caterpillar	SATO	**ZF**	TE-ML 06E
Claas	CVT	**ZF**	TE-ML 06F
Deutz	Allis AC Power Fluid 821 XL	**ZF**	TE-ML 06K
Fendt	FWN 81001	**ZF**	TE-ML 06L
Fendt	Vario	**ZF**	TE-ML 06M
John Deere	Hygard	**ZF**	TE-ML 06N
John Deere	JDM J20C	**ZF**	TE-ML 06P
Komatsu	KES 07.866	**ZF**	TE-ML 06R
Kubota	UDT	**ZF**	TE-ML 06S
Kubota	UDT-HD	**ZF**	TE-ML 06T
Massey Ferguson	CMS M 1135	**ZF**	TE-ML 17E
Massey Ferguson	CMS M 1141	**ZF**	TE-ML 21F

Properties

	Method	*Unit*	*Typical*
Viscosity Grade	*SAE J300*	*SAE*	*10W-30*
Viscosity Grade	*SAE J306*	*SAE*	*75W-85*
Density, 15 °C	*D 4052*	*g/ml*	*0,861*
Density, 20 °C	*D 4052*	*g/ml*	*0,858*
Kinematic Viscosity, 40 °C	*D 445*	*mm²/s*	*71.1*
Kinematic Viscosity, 100 °C	*D 445*	*mm²/s*	*12.0*
Viscosity Index	*D 2270*	*-*	*166*
Brookfield Viscosity, -20 °C	*D 2983*	*Pa.s*	*3,4*
Pour Point	*D 97*	*°C*	*-42*
Flash Point, COC	*D 92*	*°C*	*240*

The figures above are not a specification. They are typical figures obtained within production tolerances.

Sustainability

*The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 T 2300 CVT 10W-30 is **1.30** kg CO_2eq / kg.*
Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.
For more info check here

we take care