

Q8 Ravel TX 630

Dewatering anti-corrosion fluid

Description

Q8 Ravel TX 630 is a temporary anti-corrosion fluid with good dewatering properties for ferrous tubes, pipes, bars, profiles, sheets, strips, rods and other mechanical parts. It provides a high quality medium term protection against corrosion, especially for indoor intermediate storage. Depending on the application method, the product will leave an oily protection film. The product is free of solvents and has a high flash point, guaranteeing a minimal fire hazard and improved operator working conditions.

Applications

Q8 Ravel TX 630 is a high quality indoor protection fluid for non-ferrous and ferrous components and assemblies where the use of a solvent cutback product is not permitted because of fire hazards. The product will quickly remove water moisture from the metal surface of components such as injectors, pipes, profiles, tubes, strip, sheets, bars, rods and mechanical parts. It is designed for use in cold non-deformation, finishing operations. Q8 Ravel TX 630 can be applied by dipping, rolling or spraying leaving a thin oily layer. The water removing properties are more effective when the components are dipped into the oil tank. It can be easily removed with a solvent or alkaline cleaner.

User instructions

In order to preserve the integrity of this product drums should be stored inside a building protected from frost and direct sunlight.

Environment, Health and Safety

Please consult the Material Safety Data Sheet for instructions regarding safe handling and environmental issues.

Properties

	Method	Unit	Typical
Appearance	Visual	-	Clear brownish fluid
Density, 15 °C	D 4052	g/ml	0.87
Kinematic Viscosity, 40 °C	D 445	mm ² /s	23
Flash Point, COC	D 92	°C	190

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Please contact your Q8Oils representative for further advice and support on your specific application and equipment.

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q8Oils state of the art facility in Belgium), of Q8 Ravel TX 630 is **1.27** kg CO₂eq / kg.

Please contact Q8Oils to learn more about the positive environmental impact, the handprint, of this product.

For more info check here



**we
take
care**