

## Q8 Formula V 5W-40

Synthetic VW 508.88/509.99 passenger car engine oil

### Description

Q8 Formula V 5W-40 is a synthetic allround high SAPS engine oil for passenger cars and light duty commercial vehicles. This product guarantees advanced engine protection and facilitates easy starting at low temperatures. It is designed to counter sludge formation and minimizes oil consumption. It meets the requirements of API SN and VW 508.88/509.99

### Applications

Q8 Formula V 5W-40 is specially formulated for Volkswagen passenger car gasoline and diesel engines requiring VW 508.88/509.99.

### Benefits

- Outstanding oil film strength under all engine operating conditions.
- Outstanding engine protection after cold starting.
- Excellent protection against rust and corrosion.
- Outstanding friction reduction.

### Specifications, recommendations and approvals

ACEA	A3/B4	Renault	RN 0700
API	SN	Renault	RN 0710
MB	226.5	VAG	VW 508.88
MB	229.5	VAG	VW 509.99
Porsche	A40		

### Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,848
Viscosity Grade	-	-	5W-40
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	79
Kinematic Viscosity, 100 °C	D 445	mm <sup>2</sup> /s	13.6
Viscosity Index	D 2270	-	174
Pour Point	D 97	°C	-45
Sulfated Ash	D 874	% mass	1.3
Viscosity at high temp. & high shear rate (HTHS)	CEC-L-36-A-90	mPa.s	>=3.5

The figures above are not a specification. They are typical figures obtained within production tolerances.