Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

# SAFETY DATA SHEET

Q8 Terra 2500 UTTO



1.1 Product identifier	
Product name	: Q8 Terra 2500 UTTO
1.2 Relevant identified uses	f the substance or mixture and uses advised against
Material uses	: Lubricating oil for tractor transmissions
1.3 Details of the supplier of	he safety data sheet
Supplier	: Kuwait Petroleum Companies in the Benelux Company Office: Desguinlei 100 - 8, 2018 Antwerp, Belgium Contactaddress: Petroleumkaai 7, 2020 Antwerp, Belgium Tel. +32 3 247 38 11, Fax +32 3 216 03 42
Manufacturer / Distributor	: Kuwait Petroleum Belgium N.V./S.A. / Q8Oils Italia S.r.I. Petroleumkaai 7 Via Volpedo 2 B-2020 Antwerp Belgium I5050 Castellar Guidobono (AL) Italy
e-mail address of person responsible for this SDS	: SDSinfo@Q8.com, communication preferably in English only.
PCN Information contact	: PCNinfo@Q8.com, communication preferably in English only.
1.4 Emergency telephone nu	ıber
Europe	: +44 (0) 1235 239 670 CARECHEM24
Global (English only)	: +44 (0) 1865 407 333
National advisory body/Poi	on Center
Belgium	: Poison Centre : +32 (0)70 245 245
SECTION 2: Hazards	identification
2.1 Classification of the subs	ance or mixture
Product definition	: Mixture
Classification according to KIN SENSITIZATION	Regulation (EC) No. 1272/2008 [CLP/GHS] Category 1 H317
The product is classified as h	zardous according to Regulation (EC) 1272/2008 as amended.
Ingredients of unknown toxicity	: None.
Ingredients of unknown ecotoxicity	: None.
See Section 16 for the full tex	of the H statements declared above.
See Section 11 for more deta	ed information on health effects and symptoms.
2.2 Label elements	
Hazard pictograms	
Signal word	: Warning

 Date of issue/Date of revision
 : 20-11-2024
 Date of previous issue
 : 04-11-2024

**Hazard statements** 

: 🕅 317 - May cause an allergic skin reaction.

## **SECTION 2: Hazards identification**

Precautionary statements		
i i countionary statements		
Prevention	:	₱280 - Wear protective gloves. P261 - Avoid breathing vapor.
Response	:	₱302 + P352 - IF ON SKIN: Wash with plenty of water. P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention. P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	:	Not applicable.
Disposal	:	₱501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Benzenesulfonic acid, propenated, calcium salt, overbased
Supplemental label elements	1	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	ner	<u>its</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Prolonged or repeated contact may dry skin and cause irritation.
Hazardous ingredients Supplemental label elements Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles <u>Special packaging requirem</u> Containers to be fitted with child-resistant fastenings Tactile warning of danger 2.3 Other hazards Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII Other hazards which do	: : : :	national and international regulations. Benzenesulfonic acid, propenated, calcium salt, overbased Not applicable. Not applicable. Not applicable. Not applicable. This mixture does not contain any substances that are assessed to be a PBT over vPvB.

## **SECTION 3: Composition/information on ingredients**

: Mixture				
Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
-	≥50 - ≤75	Not classified.	-	[2]
-	≥25 - ≤50	Asp. Tox. 1, H304	-	[1] [2]
REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8	<2.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411	-	[1]
REACH #: 01-2119657986-16 EC: 701-205-4 CAS: 68610-84-4	≤3	Skin Sens. 1, H317 Aquatic Chronic 4, H413	-	[1]
REACH #: 01-2119452498-28 EC: 201-297-1	≤0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317	-	[1] [2]
	Identifiers  - REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8 REACH #: 01-2119657986-16 EC: 701-205-4 CAS: 68610-84-4 REACH #: 01-2119452498-28	Identifiers%- $\geq 50 - \leq 75$ - $\geq 25 - \leq 50$ - $\geq 25 - \leq 50$ REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8 $<2.5$ REACH #: 01-2119657986-16 EC: 701-205-4 CAS: 68610-84-4 $\leq 3$ REACH #: 01-2119452498-28 $\leq 0.1$	Identifiers%Classification- $\geq 50 - \leq 75$ Not classified $\geq 25 - \leq 50$ Asp. Tox. 1, H304- $\geq 25 - \leq 50$ Asp. Tox. 1, H304REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8 $< 2.5$ Eye Dam. 1, H318 Aquatic Chronic 2, H411REACH #: 01-2119657986-16 EC: 701-205-4 CAS: 68610-84-4 $\leq 3$ Skin Sens. 1, H317 Aquatic Chronic 4, H413REACH #: 01-2119452498-28 $\leq 0.1$ Flam. Liq. 2, H225 Skin Irrit. 2, H315	Identifiers%ClassificationSpecific Conc. Limits, M-factors and ATEs- $\geq 50 - \leq 75$ Not classified $\geq 25 - \leq 50$ Asp. Tox. 1, H304 $\geq 25 - \leq 50$ Asp. Tox. 1, H304-REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8 $\leq 2.5$ Eye Dam. 1, H318 Aquatic Chronic 2, H411-REACH #: 01-2119657986-16 EC: 701-205-4 CAS: 68610-84-4 $\leq 3$ Skin Sens. 1, H317 Aquatic Chronic 4, H413-REACH #: 01-2119452498-28 $\leq 0.1$ Flam. Liq. 2, H225 Skin Irrit. 2, H315-

## Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

Q8 Terra 2500 UTTO

# SECTION 3: Composition/information on ingredients CAS: 80-62-6 STOT SE 3, H335 Index: 607-035-00-6 See Section 16 for the full text of the H statements declared above. Statements declared

\* Contains one or more of the following:

CAS: 64742-54-7, EC: 265-157-1, EU REACH: 01-2119484627-25 CAS: 64742-55-8, EC: 265-158-7, EU REACH: 01-2119487077-29 CAS: 64742-65-0, EC: 265-169-7, EU REACH: 01-2119471299-27 CAS: 72623-87-1, EC: 276-738-4, EU REACH: 01-2119474889-13

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
	ns and effects, both acute and delayed
Over-exposure signs/symp	
Eve contact	: No specific data.

Date of issue/Date of revision

SECTION 4: First aid	l measures
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	: No specific data.
4.3 Indication of any immed	ate medical attention and special treatment needed
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO <sub>2</sub> , alcohol-resistant foam or water spray (fog).
Unsuitable extinguishing media	: Do not use water jet.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident in there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures				
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.		
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		

Date of issue/Date of revision

#### **SECTION 6: Accidental release measures**

6.3 Methods and materials	for containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	<ul> <li>See Section 1 for emergency contact information.</li> <li>See Section 8 for information on appropriate personal protective equipment.</li> <li>See Section 13 for additional waste treatment information.</li> </ul>

#### **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

Protective measures	: Fut on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### 7.3 Specific end use(s)

Recommendations

: Not available.

Industrial sector specific solutions

: Not available.

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

#### **SECTION 8: Exposure controls/personal protection**

Product/ingredient name	Exposure limit values
Severely refined mineral oil (C15 - C50) * - Not	EU OEL (Europe)
classified.	TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Mist.
	STEL 15 minutes: 10 mg/m <sup>3</sup> . Form: Mist.
Severely refined mineral oil (C15 - C50) * -	EU OEL (Europe)
H304	TWA 8 hours: 5 mg/m <sup>3</sup> . Form: Mist.
	STEL 15 minutes: 10 mg/m <sup>3</sup> . Form: Mist.
methyl methacrylate	Limit values (Belgium, 5/2021)
	TWA 8 hours: 50 ppm.
	TWA 8 hours: 208 mg/m <sup>3</sup> .
	STEL 15 minutes: 416 mg/m <sup>3</sup> .
	STEL 15 minutes: 100 ppm.
	EU OEL (Europe, 1/2022)
	TWA 8 hours: 50 ppm.
	STEL 15 minutes: 100 ppm.

#### **Biological exposure indices**

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

Product/ingredient name	Туре	Exposure	Value	Population	Effects
zinc bis[O,O-bis(2-ethylhexyl)] bis	DNEL	Long term Oral	0.19 mg/	General	Systemic
(dithiophosphate)			kg bw/day	population	-
	DNEL	Long term	1.67 mg/m <sup>3</sup>	General	Systemic
		Inhalation	_	population	-
	DNEL	Long term Dermal	4.8 mg/kg	General	Systemic
			bw/day	population	-
	DNEL	Long term	6.6 mg/m <sup>3</sup>	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	9.6 mg/kg	Workers	Systemic
			bw/day		
methyl methacrylate	DNEL	Short term Dermal	1.5 mg/cm <sup>2</sup>		Local
				population	
	DNEL	Long term Dermal	1.5 mg/cm <sup>2</sup>	General	Local
				population	
	DNEL	Short term Dermal	1.5 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Dermal	1.5 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Oral	8.2 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	8.2 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term Dermal	13.67 mg/	Workers	Systemic
			kg bw/day	_	
	DNEL	Long term	74.3 mg/m <sup>3</sup>	General	Systemic
		Inhalation		population	
	DNEL	Long term	104 mg/m³	General	Local
		Inhalation		population	
	DNEL	Short term	208 mg/m <sup>3</sup>	General	Local
		Inhalation		population	l
	DNEL	Long term	208 mg/m <sup>3</sup>	Workers	Local
		Inhalation			
e of issue/Date of revision : 20-	11-2024	Date of previous issue	:04-11-2	024	Version : 1.01

SECTION 8: Exposure controls/personal protection					
DNEL	Long term Inhalation	348.4 mg/ m <sup>3</sup>	Workers	Systemic	
DNEL	Short term Inhalation	416 mg/m <sup>3</sup>	Workers	Local	

#### **PNECs**

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Wear suitable gloves tested to EN374. Recommended: < 1 hour (breakthrough time): nitrile rubber 0.17 mm. Provide employee with skin care programmes.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	<ul> <li>Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.</li> </ul>
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: Boiling point > 65 °C: A1; Boiling point < 65 °C: AX1; Hot material: A1P2. Gas and combination filter cartridges should comply with the European standard EN14387.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid. [Oily liquid.]
Appearance	: Clear
Color	: Yellow [Light]
Odor	: Slight
Odor threshold	: Not available.
Melting point/freezing point	: Not applicable.
Pour point	: -48°C (-54.4°F) [ASTM D 97]
Boiling point or initial boiling point and boiling range	: >300°C (>572°F)
Flammability	: Not applicable.
Lower and upper explosion limit	: Not available.
Flash point	: Open cup: >210°C (>410°F) [ASTM D 92] [Product does not sustain combustion. ]
Auto-ignition temperature	: >300°C (>572°F)
Decomposition temperature	: >300°C
рН	Not applicable.
Viscosity	<ul> <li>Kinematic (40°C (104°F)): 39.6 mm<sup>2</sup>/s (39.6 cSt) [ASTM D 445]</li> <li>Kinematic (100°C (212°F)): 7.7 mm<sup>2</sup>/s (7.7 cSt) [ASTM D 445]</li> </ul>
Solubility	:
Mar all a	Desult

Media		Result
cold water hot water		Not soluble Not soluble
Solubility in water	:	Not available.
Partition coefficient n-octanol/ water (log Pow)	;	Not applicable.
/apor pressure	:	<0.01 kPa (<0.075006 mm Hg)
Density	:	0.86 g/cm³ [15°C (59°F)] [ASTM D 4052]
Relative vapor density	:	Not available.
Explosive properties	1	Not applicable.
Dxidizing properties	1	Not applicable.
Particle characteristics		
Median particle size	1	Not applicable.

#### **Oxidizing properties** : Not applicable.

#### 9.2.2 Other safety characteristics

Not applicable.

**Explosive properties** 

: Not applicable.

<b>SECTION 10</b>	): Stability and	reactivity
-------------------	------------------	------------

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredie	ents.
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occu	ır.
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: Reactive or incompatible with the following materials: Strong oxidizing materials	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition produce should not be produced.	sts

## **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure	
Severely refined mineral oil (C15 - C50) * - Not classified.	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours	
	LD50 Dermal	Rabbit	>5000 mg/kg	_	
	LD50 Oral	Rat	>5000 mg/kg	-	
Severely refined mineral oil (C15 - C50) * - H304	LC50 Inhalation Dusts and mists	Rat - Male, Female	5.53 mg/l	4 hours	
,	LD50 Dermal LD50 Oral	Rabbit Rat	>5000 mg/kg >5000 mg/kg	-	
zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	LD50 Dermal	Rabbit	>5 g/kg	-	
	LD50 Oral	Rat	3.1 g/kg	-	
methyl methacrylate	LC50 Inhalation Vapor	Rat	78000 mg/m <sup>3</sup>	4 hours	
	LD50 Dermal LD50 Oral	Rabbit Rat	>5 g/kg 7872 mg/kg	-	

**Conclusion/Summary** 

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Severely refined mineral oil (C15 - C50) * - Not classified.	N/A	N/A	N/A	N/A	5.53
Severely refined mineral oil (C15 - C50) * - H304 zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) methyl methacrylate	N/A 3100 7872	N/A N/A N/A	N/A N/A N/A	N/A N/A 78	5.53 N/A N/A

Irritation/Corrosion

### **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Severely refined mineral oil (C15 - C50) * - Not classified.	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days
Severely refined mineral oil (C15 - C50) * - H304	Eyes - Iris lesion	Rabbit	0	48 hours	72 hours
, , , , , , , , , , , , , , , , , , ,	Eyes - Redness of the conjunctivae	Rabbit	0.33	48 hours	72 hours
	Skin - Edema	Rabbit	0	72 hours	7 days
	Skin - Erythema/Eschar	Rabbit	0.17	72 hours	7 days

#### **Conclusion/Summary**

```
Eyes
```

: Non-irritating to the eyes.

: Not available.

The eye irritation hazard is based on an evaluation of the data for similar products. These data show that a specific component present in this product antagonizes (or decreases the severity of) the eye irritation of the ZnDTP.

#### **Respiratory or skin sensitization**

Product/ingredient name	Route of exposure	Species	Result
Severely refined mineral oil (C15 - C50) * - Not classified.	skin	Guinea pig	Not sensitizing
Severely refined mineral oil (C15 - C50) * - H304	skin	Guinea pig	Not sensitizing
Conclusion/Summary	: Not available.	·	·

**Conclusion/Summary** 

#### **Mutagenicity**

Product/ingredient name	Test	Experiment	Result
Severely refined mineral oil (C15 - C50) * - Not classified.	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative
Severely refined mineral oil (C15 - C50) * - H304	474 Mammalian Erythrocyte Micronucleus Test	Experiment: In vivo Subject: Mammalian-Animal Cell: Somatic	Negative

#### **Conclusion/Summary**

#### **Carcinogenicity**

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - Not classified. Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal - TC Negative - Dermal - TC	Mouse - Female Mouse - Female	-	78 weeks 78 weeks

#### **Conclusion/Summary** : Not available.

#### **Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-
Severely refined mineral oil (C15 - C50) * - H304	Negative	Negative	Negative	Rat - Male, Female	Oral: 1000 mg/ kg	-

## **SECTION 11: Toxicological information**

Conclusion/Summary

: Not available.

**Teratogenicity** 

Toratogomony				
Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - Not classified.	Negative - Dermal	Rat	2000 mg/kg	7 days per week
Severely refined mineral oil (C15 - C50) * - H304	Negative - Dermal	Rat	2000 mg/kg	7 days per week

**Conclusion/Summary** : Not available.

#### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
methyl methacrylate	Category 3		Respiratory tract irritation

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Product/ingredient name	Result
Severely refined mineral oil (C15 - C50) * - H304	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	:	Not available.
Potential acute health effects	2	
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion	1	No known significant effects or critical hazards.
Symptoms related to the phy	sic	cal, chemical and toxicological characteristics
Eye contact	:	No specific data.
Inhalation	:	No specific data.
Skin contact	:	Adverse symptoms may include the following: irritation redness dryness cracking
Ingestion	1	No specific data.
Delayed and immediate effect	ts	and also chronic effects from short and long term exposure
Short term exposure		
Potential immediate effects	:	Not available.
Potential delayed effects	:	Not available.
<u>Long term exposure</u>		
Potential immediate effects	1	Not available.
Potential delayed effects	:	Not available.
Potential chronic health effe	ect	<u>s</u>

## **SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
Severely refined mineral oil (C15 - C50) * - Not classified.	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week
Severely refined mineral oil (C15 - C50) * - H304	Sub-acute LOAEL Oral	Rat - Male	125 mg/kg	13 weeks; 5 hours per day
, , , , , , , , , , , , , , , , , , ,	Sub-chronic NOAEL Oral	Rat - Male, Female	≥2000 mg/kg	13 weeks; 5 days per week
	Sub-acute NOAEL Inhalation Vapor	Rat - Male	>980 mg/m³	4 weeks; 5 days per week
Conclusion/Summary	: Not available.			
General	<ul> <li>Prolonged or repeated conta or dermatitis. Once sensitiz subsequently exposed to ve</li> </ul>	ed, a severe alle		
Carcinogenicity	: No known significant effects	or critical hazar	ds.	
Mutagenicity	: No known significant effects	or critical hazar	ds.	
Reproductive toxicity	: No known significant effects	or critical haza	ds.	

#### 11.2 Information on other hazards

#### **11.2.1 Endocrine disrupting properties**

Not available.

#### 11.2.2 Other information

Not available.

### **SECTION 12: Ecological information**

#### **12.1 Toxicity**

Result	Species	Exposure
Acute NEL >100 mg/l Fresh water	Algae	72 hours
Acute NEL >10000 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i>	48 hours
Acute NEL ≥100 mg/l Fresh water	Fish - Pimephales promelas	96 hours
Chronic NEL 10 mg/l Fresh water	Daphnia - Daphnia magna	21 days
Acute NEL >100 mg/l Fresh water	Algae	72 hours
Acute NEL >10000 mg/l Fresh water	Daphnia - <i>Daphnia Magma</i>	48 hours
		96 hours
		21 days
Acute LC50 130000 µg/l Fresh water	Fish - <i>Pimephales promelas</i> - Adult	96 hours
	Acute NEL >100 mg/l Fresh water Acute NEL >10000 mg/l Fresh water Acute NEL ≥100 mg/l Fresh water Chronic NEL 10 mg/l Fresh water Acute NEL >100 mg/l Fresh water Acute NEL >10000 mg/l Fresh water Acute NEL ≥1000 mg/l Fresh water Chronic NEL 10 mg/l Fresh water	Acute NEL >100 mg/l Fresh waterAlgaeAcute NEL >10000 mg/l Fresh waterAlgaeAcute NEL ≥100 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL ≥100 mg/l Fresh waterDaphnia - Daphnia magnaAcute NEL >100 mg/l Fresh waterAlgaeAcute NEL >1000 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL >1000 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL >10000 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL ≥1000 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL ≥100 mg/l Fresh waterDaphnia - Daphnia MagmaAcute NEL ≥100 mg/l Fresh waterDaphnia - Daphnia magnaAcute LC50 130000 µg/l Fresh waterDaphnia - Daphnia magnaAcute LC50 130000 µg/l Fresh waterFish - Pimephales promelas

#### **Conclusion/Summary**

#### **12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
Źſnc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	-	5 % - 27 days	-	-

**Conclusion/Summary** 

: Not available.

SECTION 12: Ecological information			
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Severely refined mineral oil (C15 - C50) * - Not classified.	-	-	Inherent
Severely refined mineral oil (C15 - C50) * - H304	-	-	Inherent
zinc bis[O,Ó-bis (2-ethylhexyl)] bis (dithiophosphate)	-	-	Not readily

#### **12.3 Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Znc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate) Benzenesulfonic acid, propenated, calcium salt, overbased	3.59 -	- 64	Low
methyl methacrylate	1.38	-	Low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Not available.

#### 12.7 Other adverse effects

No known significant effects or critical hazards.

#### **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### **13.1 Waste treatment methods**

Product	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

#### Hazardous waste

#### European waste catalogue (EWC)

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils

#### **Packaging**

## Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878 - Belgium

Q8 Terra 2500 UTTO

#### **SECTION 13: Disposal considerations**

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	Fhis material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Maritime transport in** : Not available. bulk according to IMO instruments

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

#### Substances of very high concern

None of the components are listed.

## Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Product/ingredient name		%	Designation [Usage]	
🛿 8 Terra 2500 UTTO		≥90	3	
Labeling	: Not applicat	ole.		
Other EU regulations				
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			

#### 2020/878 - Belgium Q8 Terra 2500 UTTO SECTION 15: Regulatory information **Industrial emissions** : Not listed (integrated pollution prevention and control) -Water **Explosive precursors** : Not applicable. Ozone depleting substances (1005/2009/EU) Not listed. Prior Informed Consent (PIC) (649/2012/EU) Not listed. Persistent Organic Pollutants (1021/2019/EU) Not listed. **Seveso Directive** This product is not controlled under the Seveso Directive. **National regulations Germany** Hazard class for water : 1 (WGK) **Switzerland VOC content** : Exempt. International regulations Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed. **Montreal Protocol** Not listed. Stockholm Convention on Persistent Organic Pollutants Not listed.

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Inventory** list

ł	<u>Inventory list</u>		
	Australia	:	All components are listed or exempted.
	Canada	:	All components are listed or exempted.
	China	:	Not determined.
	Eurasian Economic Union	:	Russian Federation inventory: Not determined.
	Japan	;	Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): Not determined.
	New Zealand	:	All components are listed or exempted.
	Philippines	:	All components are listed or exempted.
	Republic of Korea	:	All components are listed or exempted.
	Taiwan	:	All components are listed or exempted.
	Thailand	:	Not determined.
	Turkey	:	Not determined.
	United States of America	:	All components are active or exempted.
	Viet Nam	:	Not determined.

## **SECTION 15: Regulatory information**

15.2 Chemical Safety	: Chemical Safety Assessments for all substances in this product are either Complete
Assessment	or Not applicable.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.		Indicates information	h that has changed from	previously issued version.
--	--	-----------------------	-------------------------	----------------------------

Indicates information	on that has changed from previously issued version.
Abbreviations and acronyms	: ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
	ASTM = American Society for Testing and Materials
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DIN = German Institute for Standardization
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EC = European Commission
	EC50 = Half maximal effective concentration
	EN = European Standard (Norm)
	EUH statement = CLP-specific Hazard statement
	GHS - Globally Harmonized System of Classification and Labeling of Chemicals IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IC50 = Half maximal inhibitory concentration
	IMDG = International Maritime Dangerous Goods
	IMO = International Maritime Organisation
	ISO = International Organization for Standardization
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LOAEL / LOAEC = Lowest Observed Adverse Effect Level / Concentration
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	N/A = Not available
	NOAEL / NOAEC = No Observed Adverse Effect Level / Concentration
	NOEL / NOEC = No Observed Effect Level / Concentration
	OECD = Organisation for Economic Co-operation and Development
	OEL = Occupational Exposure Limit PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	Regulation [Regulation (EC) No. 1907/2006]
	RID = The Regulations concerning the International Carriage of Dangerous Goods
	by Rail
	SDS = Safety Data Sheet
	SVHC = Substances of Very High Concern
	STEL = Short Term Exposure Limit
	TLV = Threshold Limit Value
	TWA = Time Weighted Average
	UFI = Unique Formula Identifier
	UN = United Nations
	VOC = Volatile Organic Compound
	vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification	
Skin Sens. 1, H317	Calculation method	

#### SECTION 16: Other information

The mineral base oils contained in this product are severely refined and contain less than 3% DMSO extract according to IP 346 method, and are therefore not classified as carcinogen according to Regulation (EC) No 1272/2008, note L.

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

#### Full text of abbreviated H statements

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

#### Full text of classifications [CLP/GHS]

Aquatic Chronic 2 Aquatic Chronic 4	AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 4
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1	SKIN SENSITIZATION - Category 1
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) - Category 3
Training advice	: Ensure operatives are trained to minimise exposures.
Date of printing	: 20-11-2024
Date of issue/ Date of	: 20-11-2024
revision	
Date of previous issue	e : 04-11-2024
Version	: 1.01
Prepared by	: Kuwait Petroleum Research & Technology B.V., The Netherlands
Notice to reader	

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.