

Q8 Formula Exclusive V 0W-30

Synthetic VW 504.00/507.00 passenger car engine oil

Description

Q8 Formula Exclusive V 0W-30 is an exceptional performance, low SAPS engine oil, meeting the VW 504.00/507.00 and ACEA C3 standard. This product provides excellent protection against wear, enhanced durability and fuel economy.

Applications

Q8 Formula Exclusive V 0W-30 is designed for Euro 5 and 6 engines requiring VW 504.00/507.00, Porsche C30 and ACEA C3. It is developed for passenger cars and commercial vehicles with normally aspirated or turbo-charged gasoline, LPG or diesel Euro 5 & Euro 6 engines requiring low SAPS engine oil.

Benefits

- Exceptional engine protection caused by stable viscosity during total service of the oil.
- Best-in-class wear prevention ensuring long engine life.
- Superior oxidation stability
- Superior protection for exhaust catalyst and diesel particulate filter.
- Fuel economy improvement of 1% or more

Specifications, recommendations and approvals

ACEA	C3	МВ	Approval 229.51 *
BMW	Longlife-04	Porsche	C30
BMW	Longlife-12 FE	VAG	VW 504.00
BMW	Longlife-19 FE	VAG	VW 507.00
МВ	229.52 *		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 20 °C	D 4052	g/ml	0.840
Density, 15 °C	D 4052	g/ml	0,843
Viscosity Grade	-	-	0W-30
Kinematic Viscosity, 40 °C	D 445	mm²/s	61.3
Kinematic Viscosity, 100 °C	D 445	mm²/s	12.4
Viscosity Index	D 2270	-	205
Flash Point, COC	D 92	°C	210
Pour Point	D 97	°C	-48
Sulfated Ash	D 874	% mass	0,78

The figures above are not a specification. They are typical figures obtained within production tolerances.

^{*} Pending approval

Sustainability

The product Carbon Footprint (PCF), cradle-to-gate (Q80ils state of the art facility in Belgium), of Q8 Formula Exclusive V 0W-30 is **2.11** kg $\rm CO_2 eq / kg$. Please contact Q80ils to learn more about the positive environmental impact, the handprint, of this product. For more info check here

